NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	LL REPORT MULT	101	2 - 7 '	da.
STATE OF STA	F OREGON pe or print) above this line) State Permit N G-3761	, G-	345	3
(1) OWNER:	(11) LOCATION OF WELL:			
Name REYNOLDS METALS CO	County MOLT. Driller's well no	ımbar	420	60
Address TROUTDALE, ORE,	1 1 2 11 50			
Audress //2001 Office, area				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well Deepening . Reconditioning . Abandon				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	PACKFILLED TO			
Rotary Driven Demostic Daniering D	(12) WELL LOG: Diameter of well below casing			
Cable D. Jetted D. Dollestic Dimestral M. Municipal Dug Bored D. Irrigation D. Test Well Dother	Depth drilled 303 ft. Depth of compl	eted well	ス	79 ft.
	Formation: Describe color, texture, grain size			
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratu with at least one entry for each change of form			
12 " Diam. from 0 ft. to 279 ft. Gage 330	in position of Static Water Level as drilling pro			
16 " Diam from 0 ft to 31 ft. Gage 315	MATERIAL ,	From	То	swL
" Diam. from ft. to ft. Gage	TOP 3014	0	2-	
PERFORATIONS: Perforated? Yes No.	GRIEY SAND	2	6	
Type of perforator used	BROWN SAND	6	/3	
	BLUE SILT	13	17	
	GREY SILT	17	52	
perforations from ft. to ft.	MUPDY SAND	52	79	
perforations fromft. toft.	PACKED SAND	79	102	
perforations fromft. toft.	GREY JAND SOME GRAVE	162	147	*
perforations fromft. toft.	WATER BEARING SAND	147	191	
perforations from ft. to ft.	SOME GRAVEL)			
(7) SCREENS: Well screen installed? Yes No	FINE SAND AND SILT	[9]	253	
Manufacturer's Name JOHN SON	_ SAND, SILT AND GRAVES	253	269	
Type STAINLESS STEELModel No. 153407	3/LTY CLAY	269	278	
Diam. 12 Slot size 15 Set from 151 ft. to 192 ft.	SAND AND SILT SAND SILT, SOME GRAVE	790	303	
Diam. 12. Slot size 15. Set from 2.56 ft. to 269 ft.	JATION, SILI, JUNE VIRABEL	770	.503	14.
(8) WATER LEVEL: Completed well.				
Static level /6 ft. below land surface Date 10/27/67				
Arcesian pressure lbs. per square inch Date				
	*		. `	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Wes I No If yes, by whom? STRASSER				·
545 gal./min. with // ft. drawdown after / hrs.	Work started SEPT 5 19 6 7 Complete	ed NO	2U 2	<u>- 19 6 7</u>
870 " 16 " 1 "	Date well drilling machine moved off of well	Nov	<u>′.j</u>	1967
" 1080 " 21 " /2 "	Drilling Machine Operator's Certification:			• • •
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di	rect supe	ervision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported abov knowledge and belief	e are tr	rue to m	ny best
Temperature of water 5+ Was a chemical analysis made? ☐ Yes No		Date 1	1011 21	867
A	(Drilling Machine Coerctor)	Kare www		19
(10) CONSTRUCTION:	Drilling Machine Operator's License No	54		
Well seal-Material used CEMENT GRODT	The state of the s			
Depth of seal 56 ft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off? Yes No Depth	DI Company American			
Was a drive shoe used? ⚠ Yes □ No	NAME (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? Yes M No	Address 8/10 SE SUNSET LANE, PORTLAND ORE			
Type of water? depth of strata	Audress direction of the control of the			
Method of sealing strata off	[Signed] Kobert L. Strasser			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contract		5 G	<i>i</i>
Gravel placed from ft. to ft.	Contractor's License No. 10 Date	NOU.	1-8	1967