11/3-29 D

MAR 2 1362-1	001393) INC	3-25	9 1)
File Original and Circt Copy with the STATE E GINEER WATER WE STATE ENGINEER, SALEM, OREGON STATE OF	OREGON G 2 State Permit No.		
(1) OWNER: Name CEREGHINO BROTHERS	(11) WELL TESTS: Drawdown is amount w lowered below static lev	ner BOund	
Address RT. 2 BOX 162 TROUTDALE, OREGON	Yield: 365 gal./min. with 46 ft. drawdow.	. "9	hrs.
(2) LOCATION OF WELLN E . 185th & Sandy Bly		n after	, , , , , , , , , , , , , , , , , , ,
County Plubinorial Owner's number, if any	Artesian flow g.p.m. Date		
14 14 Section 29 T. 1 N R. 3 E W.M. Bearing and distance from section or subdivision corner (TL #55)	Temperature of water 52 Was a chemical analysis ma	ıde? □ Ye	s - No
bearing and disease from section of Bastavinion courses	(12) WELL LOG: Diameter of well	10	inches.
	Depth drilled 273 ft. Depth of completed w		3 <u>ft.</u>
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each c	il and struc the materia hange of fo	ture, and il in each ormation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Top soil	0	
New Well Deepening □ Reconditioning □ Abandon □	Sandy Clay	8	60
If abandonment, describe material and procedure in Item 11.	Loose Gravel & Boulders	60	111
PROPOSED USE (check): (5) TYPE OF WELL:	Yellow Clay & Gravel Gravel	111	11/1
Domestic	Cemented Gravel	114	126
Trigation Test Well ☐ Other ☐ Dug ☐ Bored ☐	Gravel (Water Bearing	126	134
	Yellow Sand	134	138
(6) CASING INSTALLED: Threaded Welded	Cemented Gravel	138	179
10 "Diam, from 0 ft. to24817" 1/ Gage 5/16	Cemented Gravel & Sand	179	195
8." Diam. from .239 ft. to .273 ft. Gage .5/16	Gravel & Black sand (W.B.)	195	196
"Diam. fromft. toft. Gage	Gemented Gravel (Approx130)	196	211
(7) PERFORATIONS 10 Perforated? Yes UNO	Blue Clay	211	251
Type of perforator used); way dr. down Torch	Black Rock ? Water Browing	251	269 · 2 7 3
SIZE of perforations GIX 14 in. by (4 X 611 in.	Gravel Water Bearing	269	-612
96 perforations from 25 to 27t to ft 168 perforations from 180 187t to ft			
720 700 8 705 1	* From 260 to 269 Black Po	rous	
120 perforations from 190 " 195 to The 8 " "	rock Water Bearing with		
1.32 perforations xxxx The bottomto 22 ft. 1	?unlimited supply Crystal Clear and sand fre	В	
(8) SCREENS: Well screen installed ☐ Yes No			
Manufacturer's Name		 	
TypeModel No		 	
Slot size Set from ft. to ft.		<u> </u>	67
Slot size Set from ft. to ft.	Work started Aug 8 1961 Completed Oc	·Te-L-L	1961
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name		
Gravel placed fromft. toft.	Type:	H.P	
Was a surface seal provided? Yes \(\text{Ino To what depth?} \)			
Material used in seal— sand gravel and coment	Well Driller's Statement:		:
Did any strata contain unusable water?	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Type of water? Depth of strata Method of sealing strata off	MAKON BOTTNER DRILLING	COMPA	NY
	(Person firm or corporation) (Type or print)		
(10) WATER LEVELS:	Address 11544 N. E. GLISAN ST.		
Static level 59 ft. below land surface Date Artesian pressure lbs. per square inch Date	Duillouis well waves		
	Driller's well number		
Log Accepted by:	[Signed] (Well Driller)		
[Signed] Date, 19	License No. 109 Date	***************	, 19