## WATER WELL REPORT STATE OF OREGON

MULT 001491

## RECEIVED

AUG 27 1981 State Well N

State Well No. 115E-15

WATER RESOURCES DEPT
SALEM. ORFGON State Permit No.

AMMENDED REPORT - SPECIAL STA	NDARD AS PER MR. AL	PETSKA.
(1) OWNER:	(10) LOCATION OF WELL:	
Name DEUMS PARRISH	County MulTNoman Driller's well number	
Address Box 147	14 14 Section 15 T.	R. S.E. W.M.
City CORBETT State OR	Tax Lot # Co Lot Blk	Subdivision
(2) TYPE OF WORK (check):	Address at well location: CROWN BIN	it HWY
New Well □ Deepening □ Reconditioning □ Abandon □	(11) WATER LEWIS C. 1 ( )	11
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found Static level ft. below l	ft. and surface. Date 2-1-2-
Rotary Air Driven D Domestic Industrial D Municipal Rotary Mud D Dug D Irrigation D Test Well D Other	Artesian pressure lbs. pe	er square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below	casing 4
(5) CASING INSTALLED: Steel   Plastic	Depth drilled ft. Depth of completed well ft.	
Threaded   Welded   Welded   Welded   Threaded   Threaded   Welded   Threaded   Welded   Threaded   Threaded   Welded   Threaded   T	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL	From To SWL
(6) PERFORATIONS: Perforated?		
Type of perforator used SAW		
Size of perforations //8 in. by /7 in.		
perforations from <b>ZGS</b> ft. to <b>305</b> . ft.		
perforations from		
perforations from		
(7) SCREENS: Well screen installed?   Yes		
Manufacturer's Name	<b>*</b>	
Type Model No.		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level		
Was a pump test made?    Yes    Yes, by whom?		
d: gal/min. with ft, drawdown after hrs.		
H H		
Air test gal/min. with drill stem at ft. hrs.		
Bailer test gal/min. with ft. drawdown after hrs.		
Astesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started JK. 27 1980 Complete	ed Jan 2 1981
(9) CONSTRUCTION: Special standards: Yes No   Well seal—Material used CENEUT - BE NTON ITE	Date well drilling machine moved off of well	Jan 2 1981
Well sealed from land surface to 195 ft.	Drilling Machine Operator's Certification:	
Diameter of well bore to bottom of seal	This well-was constructed under my direct supervision. Materials used and information reported show are true to my best knowledge and belief.	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator) Date 6-20, 1981.	
Number of sacks of cement used in well seal .13. CEMENT, BENTOWATE	/ <del></del>	9/-
How was cement grout placed? 3 RUBBER SHOLE PACKED WERE PLACED AT 195 FT.	Drilling Machine Operator's License No	
ROUT-BENTONITE WAS DUMPED INTO PLACE		
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.	
Was a drive shoe used?  Yes Plugs Size: location ft.	Name D. V. WYLAND & CO INC	
Did any strata contain unusable water?	(Person, firm or corporation)	(Type or print)
Type of Water? CONTAMINATED depth of strata /3  Method of sealing strata off	Address 16.150 SE NORMARP MILLIAUKIE OR [Signed] Dayning J.	
Was well gravel packed? ☐ Yes Size of gravel:	(Water Well Contracto	,
Gravel placed from	Contractor's License No. 55.4 Date	20, 1981.