

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report  
are to be filed with the

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

# WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

# RECEIVED

OCT 07 1980

State Well No.

State Permit No.

SALEM, OREGON

25110-19  
MULT  
001693

## (1) OWNER:

Name Jim Piper  
Address 418 N.W. 6th Ave, Portland, Ore 97209

## (2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

## (3) TYPE OF WELL:

Rotary ☒ Driven ☐  
☐ Jetted ☐  
☐ Bored ☐

## (4) PROPOSED USE (check):

Domestic ☐ Industrial ☒ Municipal ☐  
Irrigation ☐ Test Well ☐ Other ☐

## (5) CASING INSTALLED:

6" Diam. from +1 ft. to 86 ft. Gage 1250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

## (6) PERFORATIONS:

Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

## (7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

## (8) WELL TESTS:

Drawdown is amount water level is  
lowered below static level

Is a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Flow test 15 gal./min. with 70 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

## (9) CONSTRUCTION:

Well seal—Material used Cement + 52 Bentonite  
Well sealed from land surface to 86 ft.  
Diameter of well bore to bottom of seal 10 in.  
Diameter of well bore below seal 6 in.  
Number of sacks of cement used in well seal 15 sacks  
How was cement grout placed? pumped

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

## (10) LOCATION OF WELL:

County Multnomah Driller's well number  
1/4 1/4 Section 19 T. 2N R. 1W W.M.

Bearing and distance from section or subdivision corner

## (11) WATER LEVEL: Completed well.

Depth at which water was first found 245 ft.

Static level 240 ft. below land surface. Date 9-30-80

Artesian pressure lbs. per square inch. Date

## (12) WELL LOG:

Diameter of well below casing 6

Depth drilled 330 ft. Depth of completed well 330 ft.

Formation: Describe color, texture, grain size and structure of materials;  
and show thickness and nature of each stratum and aquifer penetrated,  
with at least one entry for each change of formation. Report each change in  
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
BRN CLAY	2	29	
Red CLAY	29	53	
BRN CLAY	53	77	
Med BRN Rock	77	97	
GREY Rock	97	146	
BLK LAUA	146	151	
GREY Rock	151	187	
BRN LAUA	187	194	
GREY Rock	194	263	
BLK LAUA	263	268	
GREY Rock	268	297	
BLK LAUA	297	317	
GREY Rock	317	330	

Work started 9-29 1980 Completed 9-30 1980

Date well drilling machine moved off of well 9-30 1980

## Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.  
Materials used and information reported above are true to my  
best knowledge and belief.

[Signed] Don Feakui Date 10-2, 1980  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1217

## Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is  
true to the best of my knowledge and belief.

Name TURVER DRILLING Co  
(Person, firm or corporation) (Type or print)

Address RT 1 Box 522 PORTLAND, ORE 97231

[Signed] Don Feakui  
(Water Well Contractor)

Contractor's License No. 715 Date 10-2, 1980

USE ADDITIONAL SHEETS IF NECESSARY

SP\*45656-119