NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORCEIVED

STATE OF OREGON JUL 2 4 1975

State Well No. 2

(Please type or print)

(Do not write above this line)

SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Louis B. Flury	County Mult. Driller's well no	umber	
Address Rto 2 Box 142-A Portland, Oregon	% % Section 19 т. 2-N	R. 1-W	W.M.
	Bearing and distance from section or subdivisi	on corner	
(2) TYPE OF WORK (check):			
New Well 🗽 Deepening 🗌 Reconditioning 🗋 Abandon 🖯			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	OF the		
Rotary A Driven Domestic I Industrial Municipal D	r10		ft. 7_16_75
Cable			<u>/0-/</u>
inguison (less wen (outer (Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded □ Welded \(\frac{1}{2} \)	(12) WELL LOG: Diameter of well h	holow contra	_
6	Didnicted of well below cashing		
" Diam, from ft. to ft. Gage	-		
	Formation: Describe color, texture, grain size a and show thickness and nature of each strature.		
PERFORATIONS: Perforated? Ves Ves No.	with at least one entry for each change of format position of Static Water Level and indicate prin		
I salestated. [1 105 Ep 110.		-	
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Top soil	0 2	
perforations from ft. to ft.	Brown clay Red clay	2 17 17 50	
perforations from	Brown clay	17 50 50 97	
perforations from ft. to ft.	Brown sandy clay	97 12	1
(7) SCREENS: Well screen installed? ☐ Yes 🔼 No	Blue med. rock	121 16	
Manufacturer's Name	Brown med. rock	165 350	
Type Model No.	Brown lava rock	350 362	
Diam Slot size Set from ft. to ft.	Blue med. rock	362 400	
Diam. Slot size from ft. to ft.	Brown lava rock	400 412	
(8) WELL TESTS: Drawdown is amount water level is	Blue med. rock	412 485	5
lowered below static level	Black lava rock	485 489	9
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Brown med. rock	489 540	
Yield: gal./min. with ft. drawdown after hrs.	xkinuxxinuxxxxcBlue hard ro		
" " " " " " " " " " " " " " " " " " " "	Black lava rock	570 590)
air " "			
Railor test 12 gal./min. with 60 ft. drawdown after 1 hrs.			+
Artesian flow g.p.m.			
reperature of water Depth artesian flow encountered ft.	Work started C 11 Complete		
	Work started 7-14-75 19 Complete Date well drilling machine moved off of well	7-16-75	
(9) CONSTRUCTION:	Date wen driming machine moved out of wen	<u>/-10-/5</u>	19
Well seal—Material used XXXXX Cement	Drilling Machine Operator's Certification:	A:	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above are tr	crvision.
Diameter of well bore to bottom of seal	best knowledge and belief		_
Diameter of well bore below seal	[Signed] Date 7-19-7519 Date 7-19-7519		
Number of sacks of cement used in well seal 14 sacks	Drilling Machine Operator's License No. 254		
Number of sacks of bentonite used in well sealsacks			
Brand name of bentonite	Water Well Contractor's Certification:		
of waterlbs./100 gals,	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes 🏌 No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🗌 Yes 📮 No	Name Ralph Turner Drilling Co. (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rte 1 Box 141 Hillsboro, Oregon		
Method of sealing strata off		. 1	
Was well gravel packed? ☐ Yes ☐, No Size of gravel:	[Signed] (Water Well Contra	actor)	
Gravel placed from the to the state of the s	Contractor's License No. 247 Date 7:		10