NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CLIVEU

STATE OF OREGON OCT 7 1974 State Well No. 27

(Please type or print) STATE ENGINEERstate Permit (No. (Do not write above this line) SALEM. OREGO!)

. 2N/1W-19\ MULT 001696

(1) OWNER:	(10) LOCATION OF WELL:		
Name Ralph F. Spencer	County Manlt Driller's well number		
Address Rte 2 Box 203 Portland, Oregon	14 14 Section 19 T. 2-N R. 1-W	W.M.	
22002000	Bearing and distance from section or subdivision corner	73.4	
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner		
	,		
New Well \(\mathbb{Z} \) Deepening \(\precedent \) Reconditioning \(\precedent \) Abandon \(\precedent \) If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 52	ft.	
Rotary Driven Domestic Industrial Municipal	Static level 28 ft. below land surface. Dat	e 9-19-74	
Cable Jetted	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
6" Diam. from 0 ft. to 21 ft. Gage			
"Diam. from ft. Gage ft. Gage			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
Data Post Contract Co	with at least one entry for each change of formation. Report	each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-	bearing strata.	
Type of perforator used	MATERIAL From	To SWL	
Size of perforations in, by in.	Top soil 0 2	2	
DATE OF POLICE	Brown clay 2	,	
perforations fromft. toft.	<u> </u>	52	
perforations fromft. toft.		60	
perforations from ft. to ft.		65	
(7) SCREENS: Well screen installed? ☐ Yes XX No	Eluc hard room		
Manufacturer's Name	Company of the compan		
Type Model No	-	-	
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ¬☐ No If yes, by whom?			
gal./min. with ft. drawdown after hrs.			
gai./iiii. with 16. drawdown arcci 1225.	·		
7	·		
<u>"" " " " " " " " " " " " " " " " " " "</u>			
Reilex test / G gal./min. with 15ft. drawdown after 1 hrs.			
esian flow g.p.m.			
Depth artesian flow encountered ft.	Work started 9-19-74 19 Completed 9-19-74 19		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9-19-74 19		
Well seal—Material used Cement	Drilling Machine Operator's Certification: This well was constructed under my direct s	unervicion	
Well sealed from land surface to 20 ft.	Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator) Date 10-2-7,419		
Number of sacks of cement used in well seal2 sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drining Wachine Operator's Excense 100.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water 1bs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Tyes No Plugs Size: location ft.			
Did any strata contain unusable water? 🗌 Yes 🙀 No	Name Ralph Turner Drilling Co. (Type or print)		
Type of water? depth of strata	Address Rtex 1 Box 141 Hollsbor, Oregon		
Method of sealing strata off	[Signed] Salah June		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)	.¥	
Gravel placed from ft. to ft.	Contractor's License No. 247 Date 10-2-74 19		