

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the  
STATE ENGINEER, SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

WATER WELL REPORT

STATE OF OREGON  
(Please type or print)  
(Do not write above this line)

**RECEIVED**  
JUL 3 1968  
**STATE ENGINEER**  
SALEM OREGON

State Well No. 2N/1W-28

MULT  
001739

(1) OWNER:

Name Sam Sprando  
Address Rte 1 Box 1130 Portland, Oregon

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
 Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

(5) CASING INSTALLED:

Threaded  Welded   
6" Diam. from 0 ft. to 132 ft. Gage 17#  
5 9/16" Diam. from 0 ft. to 157 ft. Gage 10#

(6) PERFORATIONS:

Perforated?  Yes  No.

Type of perforator used  
Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No

Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 15 ft. below land surface Date 6-24-68  
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom?  
g.p.m. with ft. drawdown after hrs.  
Baller test 20 gal./min. with 100 ft. drawdown after 1 hrs.  
Artesian flow g.p.m. Date  
Temperature of water Was a chemical analysis made?  Yes  No

(10) CONSTRUCTION:

Well seal—Material used Bentonite  
Depth of seal 132 feet ft.  
Diameter of well bore to bottom of seal 9" in.  
Were any loose strata cemented off?  Yes  No Depth  
Was a drive shoe used?  Yes  No  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Mult. Driller's well number  
97231 1/4 1/4 Section 28 T. 2N R. 1W W.M.  
Bearing and distance from section or subdivision corner  
Tax lot 34  
1968 Assessors Map

(12) WELL LOG:

Diameter of well below casing 6 inch

Depth drilled 190 ft. Depth of completed well 190 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top soil	0	2	
Yellow sandy clay	2	60	
Yellow fine sand	60	130	
Blue basalt	130	140	
Blue fine sand (silt)	140	150	
Blue hard rock	150	160	
Blue pours lava rock	160	190	

Work started 6-24-68 19 Completed 6-26-68 19  
Date well drilling machine moved off of well 6-26-68 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ralph Turner Date 7-1, 1968  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Ralph Turner Drilling Co  
(Person, firm or corporation) (Type or print)

Address Rte 1 Box 141 Hillsboro, Oregon

[Signed] Ralph Turner  
(Water Well Contractor)

Contractor's License No. 247 Date 7-1, 1968