DEC 1 4 1959
STATE ENGINEER WATER WELL REPORT OC2184 ate Well No.

	E OF OREGON (5) 127 State Permit No.	, 104	16	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount	water lev	al ie	
Name Melvin Gradin	10 wered below static le		c1 18	
Address Rt. 2, Gresham, Oregon	was a pump test made? ★ Yes No If yes, by whore Yield: 180 gal./min. with 214 ft. drawdow		<u> </u>	
	" " " " " "	n after	hrs.	
(2) LOCATION OF WELL:	22 22 23		11	
ΛΛ · λ	Bailer test gal./min. with ft. drawdow	n after	hrs.	
	Artesian flow		111.5.	
34 34 Section T. R. W. Bearing and distance from section or subdivision corner	7.M. Temperature of water Was a chemical analysis ma	ade? 🗆 Y	Zes □ No	
bearing and distance from section of subdivision corner				
	1 . .	Depth drilled 452 ft. Depth of completed well 282 ft.		
	700			
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each colors.	l and stru the mater	icture, and	
	stratum penetrated, with at least one entry for each c	hange of	formation.	
	MATERIAL	FROM	TO	
(3) TYPE OF WORK (check):	Clay	0	62	
New Well ☐ Deepening ☐ Reconditioning ☐ Abando	□ Cemented Gravel	62	81	
If abandonment, describe material and procedure in Item 11.	Cemented Gravel & boulders	81	90_	
PROPOSED USE (check): (5) TYPE OF WELL	. Clay and gravel	90	98	
	Cemented Gravel	98_	104	
Cable Jetted	□ Some boulders	104	115	
Irrigation 1 Test well Other Dug Bored	Cemented Gravel	115	120	
(6) CASING INSTALLED: Threaded Welded 3	Some water	120	140	
10 "Diam. from 0 ft. to 285 ft. Gage 331b/	ft Tighter formation	_140_	179	
	Clay and grayol	_179	185	
	Very tight formation	185	197	
	_ Large gravel with clay	197	223	
(7) PERFORATIONS: Perforated? LY Yes No	Small amount of loose grave	_223_	242	
Type of perforator used Star	Hard boulders		250	
SIZE of perforations 3/8 in. by 1½ in.	Sticky brown clay	250	253	
20 perforations from 180 ft. to 197		253	288	
20 perforations from 200 ft. to 216		288	295_	
20 perforations from 223 ft. to 229		295	315	
perforations from 230 ft. to 240 perforations from 278 ft. to 278	ft. Brown clay with gravel	1	330	
40 perforations from 24.0 it. to 24.8			385	
(8) SCREENS: Well screen installed Yes No	- Shale	_385	443	
Manufacturer's Name			· · · · · · · · · · · · · · · · · · ·	
Type Model No	Cement olna at 235'			
Slot size Set from ft. to				
A Slot size Set from ft. to	ft. Work started February 19 59 Completed Ju	une	1959	
(9) CONSTRUCTION:		****		
Was well gravel packed? Yes No Size of gravel:	(13) PUMP:			
Gravel placed fromft. toft.	Manufacturer's Name			
Was a surface seal provided? ☐ Yes ☐ No To what depth?	ft. Type: H	.P	**	
Material used in seal—	Well Driller's Statement:			
Did any strata contain unusable water? 🔲 Yes 🔲 No	This well was drilled under my jurisdiction ar	A 41-2-		
Type of water? Depth of strata	true to the best of my knowledge and belief.	id this r	eport is	
Method of sealing strata off				
(10) WATER LEVELS:	NAME R. J. STRASSER DRILLING CO. (Person, firm, or corporation)	e or print)	
Static level 62 ft. below and surface Date	Address 8110 S. E. Sunset Lane, Po			
Artesian pressure lbs. per square inch Date				
The contract fraction of the contract fraction	Driller's well number4009		•·-·	
Log Accepted by:	[Signed] Kaben L. Strass	en		
[Signed] Date	(Well Driller)	F	**********	
(Owner)	License No		19 59	