The original and first copy of this report are to be filed with the		1/4-666	
STATE ENGINEER, SALEM, OREGON 97310 NOV 20 1970 plans type within 30 days from the date STATE ENGINEER and well completion.	on print	1	
SALEM OREGON			
(1) OWNER:	(10) LOCATION OF WELL:		
Name RICHARD UNIS	County MULT: Driller's well number 5763		
Address R#3 Box 24A	NW 14 NW 14 Section & T. /S	R. 4E W.M.	
TROUTDALE ORE	Bearing and distance from section or subdivision	n corner	
(2) TYPE OF WORK (check):			
New Well ✓ Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /04 ft.		
Rotary Driven Domestic M Industrial Municipal D	Static level 3/ 3 ft. below land surface. Date 1/4/70		
Cable	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded Welded (12) WELL LOG: Diameter of well below casing			
" Diam. from	Depth drilled 128 ft. Depth of completed well 128 ft.		
"Diam. from	Formation: Describe color, texture, grain size a	nd structure of materials;	
Diani, Ironi It. W It. Gage	and show thickness and nature of each stratum with at least one entry for each change of format	ion. Report each change in	
(6) PERFORATIONS: Perforated? Yes \square No.	position of Static Water Level and indicate princ	cipal water-bearing strata.	
of perforator used STAR	MATERIAL	From To SWL	
Size of perforations 3/8 in. by //4 in.	PACKED SAND	0 28	
250 perforations from 10 ft. to 120 ft.	LOOSE SAND, SMALL GRAVE		
perforations fromft. toft,	SILT AND SAND	46 104	
perforations from ft. to ft.	SAND AND GRAVEL	104 128	
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
TypeModel No			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.		9L 9	
ON WITH TESTS. Drawdown is amount water level is			
lowered below static level	<u> </u>		
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.	The Table 1		
н - н н н	The state of the s		
" "	The state of the s		
Bailer test 60 gal./min. with / ft. drawdown after 4 hrs.	The state of the s		
Artesian flow g.p.m.			
Temperature of water Depth artesian flow encountered ft.	Work started Oct 7 3 19 70 Complete		
CONSTRUCTION:	Date well drilling machine moved off of well	NOU.10 1970	
OFMENT GROUT	Drilling Machine Operator's Certification:		
3-0	This well was constructed under my	direct supervision.	
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	A .	
Diameter of well bore below seal	[Signed] Gan Baker	Date Noulb 1970	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	102	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:	·	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name KJS7/2/155EK //2/LUKG		
Did any strata contain unusable water? Yes No	Address 8/10 SE SUNSET LANE BRITINO ORE		
Type of water? depth of strata	Audiess W. Dak T		
Method of sealing strata off	[Signed] Kathar d. Mass (Water Well Contractor)		
Was well gravel packed? Yes No Size of gravel:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Tal 16 .70	
Gravel placed fromft. toft_	Contractor's License No. Date		
(USE ADDITIONAL SHEETS IF NECESSARY) SP*45656-119			