Duplicate with the STATE ENGINEER, SALEM, OREGON	OREGON OO254 Pate Permit No.	17 G(1)
(1) OWNER: Name A. R. BRUHN STATE ENGINEE Address Rt. 2 Box 617 ALE:: OPEGON Gresham Oregon	(11) WELL TESTS: Drawdown is amount we lowered below static lew was a pump test made? The No. If yes, by whom wield: 50 gal./min. with 1/3 ft. drawdow no. 1/2 no.	
(2) LOCATION OF WELL: County Multnomah Owner's number, if any— S.W. 4 N.E.4 Section 17 T. 1 S, R. 4 E W.M.	" 200 " 1 " Bailer te 00 gal./min. with 2 ft. drawdown	3 " n after 5 hrs. 1954,
Bearing and distance from section or subdivision corner S 52° 30' 2980 ft. from the N.E. corner, Section 17	(12) WELL LOG: Diameter of well 5. Depth drilled 422 ft. Depth of completed w	Inch w/ Linepches. en 402 ft.
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of i stratum penetrated, with at least one entry for each comments. MATERIAL	he material in each hange of formation. FROM TO
(3) TYPE OF WORK (check): New Well Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 11.	Top s åil Yellow Clay Cemented Gravel	1 3 3 60 60 161
PROPOSED USE (check): Domestic X	Fine Blk Sand Coarse Blk Sand Fine sand Coarse Blk Sand	161 164 164 177 177 179 179 195
(6) CASING INSTALLED: Threaded \(\text{Threaded} \) Welded \(\text{Z} \) 8 "Diam. from \(0 \) ft. to \(385 \) ft. Gage Stand \((6) \)" Diam. from \(ft. \) to \(ft. \) Gage	Cemented Gravel Sand & Clay Light Brown Clay	195 243 243 247 247 261
Perf "Diam from 382 ft to 402 ft Gage Standa liner (7) PERFORATIONS: Perforated? A Yes No	Fine Pea Gravel Brown Clay Red Clay Coarse Sand Stone	261 262 262 275 275 287 287 300
Type of perforator used Torch (6 Inch Liner) SIZE of perforations 1/8 in. by 12 in. PAXTEXX perforations from the standard of the standard o	Comented Gravel Coarse sand w/little Pea Grave	300 100
perf. /perfortions/row/ 24 Perf. to a ft. ft. Total perforations XXXXX 432 XXXXXXXXXXXXXXXXXXXXXXXXXXXXX	Water Bearing	,
SCREENS: Well screen installed		
Diam. Slot size Set from ft. to ft. Slot size ft. Set from ft. to ft.	Work started Feb. 5th 1954 Completed Ap	r il 6 1954
Was well gravel packed? Yes No Size of gravel: Gravel placed from ft. to Was a surface seal provided? Yes No To what depth To 36	(13) PUMP: Manufacturer's Name Myers 6 Inch Stroke Pump Type: Rod HP. 1 Pumping 200 P. Hr.	
Material used in seal—Coment Sand & Gravel Did any strata contain unusable water? ☐ Yes	Well Driller's Statement: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. THARVON TO DOMINIED WELL DRILLING	
d (10) WATER LEVELS: 25 G.P.M. Petered out estatic level 190 ft. below land surface Date 4/6/54	Address 11544 N. E. GLISAN ST.	
Log Accepted by Regulary Date Topus No. 21 10 50	[Signed] (Well Driller)	
[Signed] A. R. Bruhn Date January 31, 1959.	License No. LO9 Date Oct	L5 ₁₉ 56