1/1-35(1)

State Well No.

eu DEC 2196	WATER WEI	LL KErvin State Well No	- 201	
File Original and First Copy with the STATE ENGINEER, SALEM, OREGON	VEER STATE OF	O7 0 2 7 State 1 crimic 110.		
(1) OWNER: Name Eastside Plating Works Address 310 SE Stephens Portland, Oregon		Was a pump test made? Yes ☐ No If yes, by whom yield: 100 gal./min. with 3.5 ft. drawdown is amount we lowered below static lever of the property of the prop	n after	6 hrs.
(2) LOCATION OF WELL: County ###### Multnomathwner's num 1/4 1/4 Section T. Bearing and distance from section or subdivisis	R. W.M.	" 200 " 12 " Bailer test gal./min. with ft. drawdown g.p.m. Date Temperature of water 55 Was a chemical analysis magnetic for the state of the sta	after	hrs.
55 Stephens ST. 65 F. of los S.E. 3-1 F. T. Lot I, Block 45	approximately The adjacent Stophens Add ud.	(12) WELL LOG: Diameter of well Depth drilled 180 ft. Depth of completed w Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c MATERIAL	ell 180	<u>ft.</u>
			Surf.	7
(3) TYPE OF WORK (check):		Sand and silt Gravel and boulders	7	
New Well Deepening Recor Recor If abandonment, describe material and proced	nditioning	Brown sand	33	39
If abandonment, describe material and process		Loose gravel and sand	39	46
PROPOSED USE (check):	(5) TYPE OF WELL:	Cemented gravel	46	62
Domestic 🗌 Industrial 🛣 Municipal 🗌	Rotary Driven Cable Driven Cable Driven Cable Driven Cable Cable Driven Cable Cable	Brown sand	62	69
Irrigation Test Well Other	Dug 🗆 Bored 🗆	Gravel and sand Oclay binder)	_69	83
CARTIC TYCE ALLED.	welded [V	Cemented gravel	83 126	126 139
(6) CASING INSTALLED: The surf. The property of the surf.	180 ft. Gage 27 #/ft.	Sand with some gravel	139	154
" Diam. from ft. to	ft. Gage	Oemented gravel	154	170
"Diam. from ft. to	ft. Gage	Medium to large cemented grave	1	180
(7) PERFORATIONS:	erforated? 🔏 Yes 🗌 No	Wedtan		
Type of perforator used SIZE of perforations 3/8 in. by	1½ in.		_	
36.0 perforations 67.5 mm s. 36.0 perforations from 158.				
perforations from	ft. to ft.			
perforations from	ft. to ft.			
perforations from	ft. to ft.			
perforations from	ft. to ft.		-	<u> </u>
(8) SCREENS: Well screen Manufacturer's Name	installed		-	
Type	Model No		-	
Diam. Slot size Set from Store Set from Store Set from Store Set from Set from Store Set from	ft. to ft.	Work started Sept. 1 1960. Completed Se	pt.28	19 60
(9) CONSTRUCTION:		(13) PUMP:		
Was well gravel packed? ☐ Yes 【No Size of gravel:		Manufacturer's Name Johnston	······	7.1.
Gravel placed from ft. to ft.		Type: Submersible	н,Р	1.2
Was a surface seal provided? ☐ Yes ☐ No	To what depth? ft.	Well Driller's Statement:	•	
Material used in seal— Did any strata contain unusable water?	Yes X No	This well was drilled under my jurisdiction	and this	report is
	of strata	true to the best of my knowledge and belief.	_	
Method of sealing strata off		NAME R. J. Strasser Drilling (Person, firm, or corporation)	C ₀ .	
(10) WATER LEVELS:	nd surface Date Sept 27	(Person, firm, or corporation) 60Address8110SESunsetLane,Por	tland	
Static level 53 ft. below land surface Date Sept 21, Artesian pressure lbs. per square inch Date		Driller's well number 4102		
Log Accepted by://	/ / /	[Signed] Robert & Strage (Well Driller)	ser	
[Signed] // Date (Owner)	e 12/1 / 1960	License No. 10 Date Oct	. 1	, 1960