MULT 2745

/MULT \	
12745 stare	Well No. 1/1-3 M(3)

STATE ENGINEER, SALEM, OREGON 97810 FNGINEER OF OREGON within 30 days from the date; ATF FNGINEER type or print)

of well completion.	State Permit No		***************************************
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name CITY OF PORTLAND	Was a pump test made? Yes \(\square\) No If yes, by whom		ASSER
Address ROOM 209 CITY HALL	Yield: 600 gal./min. with 40 ft. drawdow	·	8 hrs.
DORTLAND DEF	" 380 " 54 "	All artel	3 "
(2) LOCATION OF WELL: PARKE AURITORIUM	" 2/2 " 7/		2 "
APPLIC HOUSE	Bailer test gal./min. with ft, drawdo	wn after	hrs.
County MULT, Driller's well number 4205	Artesian flow g.p.m. Date		
NW4 5 W Section 3 T. 15 R. 1 W.M.	Temperature of water 56 Was a chemical analysis r	nade? X	es □ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below to	elne	12
			۱
	Depth drilled 361 st. Depth of completed w		/ ft.
	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of	l and struc the materi	cture, and al in each
	stratum penetrated, with at least one entry for each c	hange of f	ormation.
(a) myrner Oer MODIF (.11.)	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	LODSE GRAVEL	e	
Well ▶ Deepening □ Reconditioning □ Abandon □	BROWN SAND AND BINDER		42
andonment, describe material and procedure in Item 12.	SAND, GRAVEL AND CLAY	42	45
(4) PROPOSED USE (check): (5) TYPE OF WELL:	LOOSE SAND AND GRAVEL	45	68
Domestic Industrial Municipal Rotary Driven	JAND AND GRAVEL SOME CLAS	68	77
Cable Jetted	LOOSE SAND AND GRAVEL	77	84
	GRAVEL AND SANDY CLAY	84	94
(6) CASING INSTALLED: Threaded Welded	LODSE SAND AND GRAVEL	94	101
12" Diam. from ft. to317_ ft. Gage330	GRAVEC SAND 4ND CLAP	101	115
" Diam. from ft. to ft. Gage	FINE BROWN SAND AND GRACE		147
" Diam. from ft. to ft. Gage	GRAVEL DARK GREY BINDER		188
(7) PERFORATIONS: Perforated? Yes No	COARSE SAND STONE	188	208
, , , , , , , , , , , , , , , , , , ,	LARGE GRAVEL AND SIT	708	120
Type of perforator used Size of perforations 3/8 in. by ///// in.	STICKY GREEN CLAY	220	242
640 perforations from 205 ft. to 221 ft.	SAND AND GRAVEL	228	
3 20 perforations from 246 ft, to 264 ft.	BROWN SANDY CLAY	255	<u> 255</u> 293
40 perforations from 29.3 ft. to 299 ft.	JANO AND GRAVEL	293	325
perforations from ft. to ft.	SAND BRAVEL AND CLAY	325	339
perforations from ft. to ft.	BROWN LAY	339	346
(8) SCREENS: Well screen installed? Tyes No.	GREEN CLAY	346	357
, on sometimes and 110	WEATHERED ROCK	351	361
ufacturer's Name		·	
Model No.		ĺ	
Diam. Slot size Set from ft. to ft.	Work started JULY 8 1965 Completed A	<u>5 20</u>	1965
	Date well drilling machine moved off of well Aug 3/1965		
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal CEMENT GROUT	Manufacturer's Name		
Depth of seal 32 ft. Was a packer used? 20	Type: H.P.		
Diameter of well bore to bottom of sealin.			
Were any loose strata cemented off? Yes X No Depth	Water Well Contractor's Certification:		
Vas a drive shoe used? □ Yes □ No	This well was drilled under my jurisdiction a	nd this :	eport is
Vas well gravel packed? ☐ Yes X No Size of gravel:	true to the best of my knowledge and belief.		^
Fravel placed from ft. to ft.	NAME KISTRASSER DRILLING CO		
Did any strata contain unusuable water? Yes No	(Person, film or corporation) (Type or print) Address 8/10 SE SUNSET LANE BRILADOE		
Type of water? depth of strata	Address 811L SE JUNSE! LANE	TOK!	WI-DUK
Method of sealing strata off	Drilling Machine Operator's License No	4	
(10) WATER LEVELS:	a like the		
static level 84 ft. below land surface Date $8/78/65$	[Signed] (Water Well Contractor)		
Artesian pressure lbs. per square inch Date		/3	165
		***************************************	,