TICE TO WATER WELL CONTRACTOR The original and first copy WATER WELL REPORT of this filed with the filed with the TATE ENGINEER, SALEM, OREGON STATE ENGINEER, SALEM, OREGON SALEM OF THE of this report are to be TATESOF OREGON pe or print). SALEM. ORLON fate Permit No (1) OWNER: (11) LOCATION OF WELL: PORTLAND STATE COLLEGE Name MULT Driller's well number County 1809 S.W. GTH AUE. SE 14 NE 14 Section Address PORTLAND ORE. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [ Reconditioning [ Abandon 🗆 If abandonment, describe material and procedure in Item 12. (3) TYPE OF WELL: (4) PROPOSED USE (check): BACKFILLED
Diameter of well below casing ... UP TOITE (12) WELL LOG: Rotary Driven 🔲 Domestic | Industrial | Municipal | Cable Jetted | Depth drilled ft. Depth of completed well Dug Irrigation | Test Well | Other Bored | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, ASING INSTALLED: Threaded | Welded X with at least one entry for each change of formation. Report each change 12 " Diam. from \_\_\_\_\_ ft. to \_\_\_\_ ft. Gage \_\_\_\_\_ in position of Static Water Level as drilling proceeds. Note drilling rates. 12 " Diam. from 155 ft. to 170 ft. Gage 330 MATERIAL SWL MARD PACKED 69 SAKD **PERFORATIONS:** LIGHT BROWN SAKDY SILT 69 97 Perforated? | Yes | No. EMENTED GRAVEL Type of perforator used SAND GRAVEL AND CLAY 119 Size of perforations in, by SOFT CEMENTED GRAVEL 123 125 perforations from \_\_\_\_\_ ft. to \_\_\_\_ LOOSE SAND AND GRAVEL 135 154 ...... perforations from \_\_\_\_\_\_ ft. to \_\_\_\_ ft. CEMENTED GRAVEL 159 perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. SAND, GRAUEL AND SILT 159 ..... perforations from ....... ft. to ..... ft. CEMENTED GRAVEL 217 219 perforations from \_\_\_\_\_ft. to \_\_\_\_ GREY AND GREEN CLAY 219 232 BROWN CLAY 232 240 (7) SCREENS: Well screen installed? Yes 🗆 No SMALL GRAUEL SAND ANDLONG 240 262 Manufacturer's Name EDWARD E JOHNSON Type STAINLESS STEEModel No. GREY SANDSTONE 262 268 JOFT CEMENTED GRAVEL 208 275 Diam / Slot size /00 Set from /40 ft. to /50 ft. SANDSTONE 275 286 Diam. ..... Slot size ...... Set from ..... ft. to ... 916 286 (8) WATER LEVEL: Completed well. Static level ft. below land surface Date A pressure Ibs. per square inch Date (9) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? 5TRASSER 14N 15 196 8 Completed APR 12 560 gal./min. with ft. drawdown after hrs. Date well drilling machine moved off of well 400 19 4 300 **Drilling Machine Operator's Certification:** This well was constructed under my direct supervision. Mate-Bailer test gal./min. with ft. drawdown after hrs. rials used and information reported above are true to my best knowledge and belief. Artesian flow g.p.m. Date Temperature of water 🛭 🍪 Was a chemical analysis made? 🗌 Yes 🔲 No (Drilling Machine Operator) M. Date 3 / 3 19,4 [Signed] (10) CONSTRUCTION: Drilling Machine Operator's License No. CEMENT Well seal-Material used . Depth of seal ..... FEET Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Were any loose strata cemented off? 

Yes No Depth .... STRASSEX Was a drive shoe used? XYes ☐ No Did any strata contain unusable water? 

Yes 
No Type of water? depth of strata

(USE ADDITIONAL SHEETS IF NECESSARY)

Contractor's License No. Date HPR 23

fethod of sealing strata off

ravel placed from .....

vas well gravel packed? 

Yes No Size of gravel: ....