EUE VE State Well No. 1/2-19 P FEB 7 9 1924 -WATER WELL REPOR File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE OF OREGON State Permit No. G-25/4 Drawdown is amount water level is lowered below static level Bottner ' ( Well No. 2 ) (11) WELL TESTS: (1) OWNER: □ No If yes, by whom? Drilling Co. Precision Cast Parts Corp. Was a pump test made? 🔀 Yes Name 20 ft. drawdown after gal./min. with 4600 S.E. Harney Drive Portland 6. Oregon 200 225 ,, (2) LOCATION OF WELL: ft. drawdown after hrs. Bailer test gal./min. with County Multnomah Owner's number, if anyg.p.m. Date Artesian flow % Section 19 T. 180 R. 2E. W.M. Temperature of water □ Was a chemical analysis made? □ Yes 🖈 No Bearing and distance from section or subdivision corner Part of Lot 1 of Gibson Subdivision Diameter of well inches.

ft. Depth of completed well to 205 ft. (12) WELL LOG: the J.A. Logan Track 231 Depth drilled Depth drilled 231 ft. Depth of completed well to 205 ft.

Formation: Describe by color, character, size of material and structure, and show thickness of aguifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. FROM MATERIAL Soil, brown - dark (3) TYPE OF WORK (check): Gravel, coarse, & boulders Deepening [ Reconditioning [ Abandon [7] Clay blue Clay yellow If abandonment, describe material and procedure in Item 11. (5) TYPE OF WELL: (4) PROPOSED USE (check): Sand , coarse, black & yellow Rotary Driven stic 🗌 Industrial 🔁 Municipal 🗌 2/1 Gravel, fine Cable Jetted 66 Irrigation ☐ Test Well ☐ Other 69 Sand, coarse Dug Bored 69 89 Gravel, fine (6) CASING INSTALLED: Threaded | Welded | 89 Gravel , medium, black าก8 10 "Diam. from 0 ft. to 204 ft. Gage \$275 108 114 Sand, coarse, brown " Diam. from ...... ft. to ..... ft. Gage ... Clay, yellow, sandy 114 118 " Diam. from ...... ft. to ..... ft. Gage 118 138 Gravel. medium Clay yellow & gravel medium 138 Perforated? Yes | No (7) PERFORATIONS: 151 Gravel , medium Type of perforator used Mills Knife Gravel medium comented 162 SIZE of perforations 3/8 in. by 162 Gravel, medium, brown ..... ft. to ..... \_\_60... 50 perforations from ... 175 185 Gravel, medium, gray, water 120 perforations from 90 ft. to ..... Gravel fine black water B 70 perforations from ... perforations from ... 193 Clay, yellow 215 Clay, reddish, coarse 222 perforations from ..... 222 22h Sand, white Clay, brown 2211 23] SCREENS: Well screen installed 🔲 Yes 🗶 No Manufacturer's Name ..... Waited for Test Pump Diam. \_\_\_\_ Slot size \_\_\_\_ Set from \_\_\_\_ ft. to \_\_\_\_ Delayed for: Work started Aug. 11 19 6.3 Completed Oct. 23 Diam. Slot size ..... Set from ..... ft. to ... (13) PUMP: CONSTRUCTION: Manufacturer's NameWestern Land Roller
Type: Turbine, Water lube H.P.20 Was well gravel packed? 🗌 Yes 🙀 No Size of gravel: ... Gravel placed from ...... ft. to ..... HP20-1800RPM Was a surface seal provided? 🕱 Yes 🗌 No To what depth? .....23..... ft. Motor U.S. Material used in seal— Cement & Sand Well Driller's Statement: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Did any strata contain unusable water? 🔲 Yes 🔲 No Depth of strata Type of water? Method of sealing strata off NAME HAAKON BOTTNER DRILLING COMPANY 11544 N. E. GLISAN ST. (10) WATER LEVELS:

ft. below land surface Date

lbs. per square inch Date

\_\_\_\_\_\_ Date \_\_\_\_\_\_, 19\_\_\_\_\_

Static level

Artesian pressure

Log Accepted by:

Driller's well number

License No. 109

[Signed]

PORTLAND 20, OREGON

Date NOV. 23 1965