APR 1 1 1997

STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by ORS 537.765)
SALEM, OREGON

Instructions for completing this report are on the last page of this form.

L09628

(START CARD) # 87881

(1) OWNER: Well Number	(9) LOCATION OF WELL by legal description:				
Name Central Church of the Nazarene	County Multnomahatitude Longitude Township 1 South N or S Range 2 East E or W. WM.				
Address 11605 SW 35th			<u> East</u>	_ E or \	v. WM.
City Portland State OR Zip 97219	Section 9		NE		
(2) TYPE OF WORK	Tax Lot R5 Lot			bdivision_	
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or no	carest address)971	5 SE	Powel	<u>.1 Blv</u>
(3) DRILL METHOD:		Por	<u>tland</u>	, OR	
Rotary Air Rotary Mud Cable Auger	(10) STATIC WATER LEV	VEL:		·	
Cother Holte	162 ft. below lan	d surface.	D	ate 4-3	97
(4) PROPOSED USE:	Artesian pressure	lb. per square is	nch. D	ate	
Domestic Community Industrial Irrigation	(11) WATER BEARING Z				
Thermal Injection Livestock Church					
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first f	found / 9	78'		
	Dopai at which was a war and		· · · · · · · · · · · · · · · · · · ·		
Special Construction approval Yes No Depth of Completed Well 34 ft.	From	То	Estimated	Flow Rate	SWL
Explosives used Yes No Type Amount HOLE SEAL	198	234	5		162
	130				
Diameter From To Material From To Sacks or pounds					$\neg \neg \neg$
12 0 20 Bentonite20 0 13 sacks					-
9½ 20 198 Cement 198 193 5 sacks					_
7½ 198234					
	(12) WELL LOG:				
How was scal placed: Method A B C D E	Ground Eleva	ation			
x Other Bentonite poured/cement pumped					GV17
Backfill placed from ft. to ft. Material	Material		From	To 11	SWL
Gravel placed from ft. to ft. Size of gravel	Clay brown sar		0	!	
(6) CASING/LINER:	Clay brown sar		11	20	
Diameter From To Gauge Steel Plastic Welded Threaded	gravel gray n			30	
Casing: 8 +1 198 250 🗷 🗆 🛣	Gravel gray me		30	35_	
	Lava gray soft	t,fracture	d 35		
	at times			76	
	Clay gray		76	83	
Liner: 6 +1 234 250 🗷 🗆 🛣	Conglomerate		83	128	
	Clay brown mix		128		
Final location of shoe(s) None	gravel small			148	
(7) PERFORATIONS/SCREENS:	Gravel cemente	_	148 م		
• •		NA VALUE		198	
Perforations Method	Gravel med & s		198		162
Screens Type Material Slot Tele/pipe	fine	Juliu Dionii	· · · · · · · · · · · · · · · · · · ·	230	
From To size Number Diameter size Casing Liner	Gravel med		230		162
None	GIAVET MEG				1.02
	Sicilar	Drilling, Inc.			
	1180	Molalla Ave.			
	Oregon City, OR 97045				
	Oregon	City, Ort 814			— —
		56-2683	A	-3-97	
(8) WELLTESTS: Minimum testing time is 1 hour	Date started 3-25-97	Complete		<u> </u>	
Flowing	(unbonded) Water Well Const				
Pump Bailer X Air Attesian	I certify that the work I perfe of this well is in compliance wi	th Oregon water supp	olv well cor	istruction s	tandards.
Yield gal/min Drawdown Drill stem at Time	Materials used and information	reported above are to	rue to the b	est of my k	nowledge
	and belief.				
		2016	WWC Nun	nber	23
	Signed Manin	V. Shaple	اسه	Date 4	-4-17
Temperature of water 45° Depth Artesian Flow Found	(bonded) Water Well Constru				
Was a water analysis done? Yes By whom	I accept responsibility for th	e construction, altera	tion, or aba	indonment	work
Did any strata contain water not suitable for intended use?	performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well				
Salty Muddy Odor Colored Other	construction standards. This report is true to the best of my knowledge and belief.				
Depth of strata:	WWC Number 1592				
Depth of Sciaca.	Signed Steven	C. Slans	/	Date 4	-4-97
ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT SE		OR THIRD CO	PY-CUST	OMER	
ORIGINAL & FIRST COFT-WATER RESOURCES DEFARIMENT SE	COLL COLL COLOR				