

(1) OWNER:

Name Schaeffer's Nursery
Address 16280 SE Higan Rd.
City Gresham Ore. State OR

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air Driven
Rotary Mud Dug
Cable Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Thermal:
Irrigation Withdrawal ReInjection
Other:
Piezometric Grounding Test

(5) CASING INSTALLED:

Steel Plastic
Threaded Welded
8" Diam. from 120 ft. to 320 ft. Gauge 250

LINER INSTALLED:

Steel Plastic
Threaded Welded

(6) PERFORATIONS:

Perforated? Yes No
Size of perforations in. by in.
180" perforations from 220 ft. to 250 ft.
200" perforations from 260 ft. to 510 ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Model No.
Type Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Pump test gal./min. with drill stem at ft. hrs.
Bailer test 60 Gals gal./min. with 12 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes No

Well seal—Material used Cement GROUT
Well sealed from land surface to 42' ft.
Diameter of well bore to bottom of seal 12" in.
Diameter of well bore below seal 8" in.
Amount of sealing material 36 sacks pounds
How was cement grout placed? Pumped in while Pipe Was Being Removed
Was pump installed? no Type HP Depth ft.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County Mult 1/4 of Section 15 of Township 1-S Range 3-E WM. (Township is North or South) (Range is East or West)
Tax Lot 0100 Lot Block Subdivision
MAILING ADDRESS OF WELL (or nearest address) SE. Orient Pr. Gresham Ore Next Door

(11) WATER LEVEL OF COMPLETED WELL:

Depth at which water was first found 220'
Static level 168 ft ft. below land surface. Date 6/3/83
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 320' ft. Depth of completed well 320' ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	0
Clay BROWN	2	18	0
Clay Yellow	18	65	0
Clay & Boulder	65	118	0
Cemented GRAVEL	118	220	168'
GRAVEL & Sand LOOSE	220	252	168'
Cemented GRAVEL	252	260	168'
GRAVEL LOOSE	260	310	168'
Clay BROWN	310	320	168'

8/30/01 Overwritten as possible to improve readability
-Donn Miller
Ore. Water Res. Dept

Date work started 5/1/83 /completed 6/3/83
Date well drilling machine moved off of well 6/3/83 19

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date 19

(bonded) Water Well Constructor Certification:

Bond 150 Issued by: Wells & Deposit (number) (Surety Company Name)
On behalf of BRANT Well DRILLING (type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

(Signed) Brad Brant (Water Well Constructor)

(Dated) 6/3/83