The original and first opy C WATER WELL REPORT of this report are to be filed with the AUGO - 1971 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date TE ENGINEER, SALEM OF OREGON (Do not write above this line)

State Well No.

State Permit No.

SALCM OTHER	<u>G 2014</u>			
(1) OWNER: (10) LOCATION OF WELL:				
Name COLUMBIA EDGEWATE COLF AND COUTE,	County MULT Driller's well nu	ımber	57-8	<i>(</i>
Address 2/37 NE MARINE DRIVE	SEN NEW Section 2 T. /N	R / 2	<u> </u>	W.M.
PORTLAND ORE 97211				77.12.27
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner	<u>r</u>	· · ·
•				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found //O ft.			
Rotary Driven Domestic Industrial Municipal	Static level / ft. below land surface. Date 7/19/7			
Cable Jetted	Artesian pressure lbs. per square inch. Date			
		,		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing			
12" Diam. from	Depth drilled 1.3.5 ft. Depth of completed well 13.5 ft			
16 " Diam. from	Formation: Describe color, texture, grain size and structure of materials;			
	and show thickness and nature of each stratum and aquifer penetrated,			
TO DEPUTOD A BYONG	with at least one entry for each change of forma position of Static Water Level and indicate prin			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and murcate prin	Trout wat	or-oearth	
ype of perforator used .5TAR	MATERIAL	From	То	SWL
size of perforations 3/5 in. by //4 in.	GRAVEL FILL	0	/	
480 perforations from 119 ft. to 131 ft.	SILT AND SAND		9	
perforations fromft. toft.	BLUE CLAY	9	50	
perforations from ft. to ft.	FINE SANDY SILT	50	6.5	
	PACKED SAND AND SILT	165	110	
(7) SCREENS: Well screen installed? Yes No	WATER BEAKING GRAVE	110	135	
Manufacturer's Name	CLAY AUD GRAVEL	/37	135	
Type Model No				
Diam Slot size Set from ft. to ft.	·			
Diam Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes \(\subseteq No \) If yes, by whom? \(\subseteq IRASSEI \)	₹			
Yield: 1080 gal./min. with 3/k/ft. drawdown after 4 hrs.				
" " "				
" " "				
		ļ		
Bailer test gal./min, with ft. drawdown after hrs.				
Artesian flow g.p.m.	1 11 71	<u> </u>		5 71
Depth artesian flow encounteredft.	Work started JUNE // 197/ Complete	ed JU		3 1971
(5) CONSTRUCTION:	Date well drilling machine moved off of well	JULY	r 23	19 7/
Well seal-Material used CEMENT GROUT	Drilling Machine Operator's Certification	:		
TI CII SCAI MACCIAI ASCA	This well was constructed under my	direct	t super	vision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	apove	are true	to my
	SVANDON A	Dota 1	AUG	4,071
Diameter of well bore below seal	[Signed] (Drilling Machine Operator) Date			
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No			
Number of sacks of bentonite used in well seal sacks				
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	liction a	nd this i	report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.			
Was a drive shoe used? Yes \(\subseteq \text{No Plugs} \) Size: location ft.	Name RJ STRASSER D.	RILL	IN G	6
Did any strata contain unusable water? Yes No	(Person, firm or corporation)		ype or pri	nt) NB O
Type of water? depth of strata	Address 8/10 SE SUNSETTLA	NR TO	~ ~ / CH	MO U
Method of sealing strata off	Kapel I of Man	111	B	
	[Signed] (Water Well Cont	ractor)		
Was well gravel packed? ☐ Yes [XNo Size of gravel:	Contractoria License No. 10 Date	_	4 3	6 107/