File Original and First Copy with the STATE ENGINEER

MULT

SALEM, OREGON STATE C	or G2304 state Permit No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount	water leve	l is
Name CITY OF PORTLAND (BUREAU OF PARKS)	Was a pump test made? X Yes \(\begin{array}{c} Drawdown is amount to lowered below static letter to the control of the	Aer 190	LTNER
Address CITY HALL ANNEX TO PORTLAND OREGON	Yield: 300 gal./min. with 11 ft. drawdow		_
	" 515 " 33 "	/II atter	2 hrs.
EAST DELTA PARK 10850 N DENTER ATTE	" 630 " 55 "		
(2) LOCATION OF WELL TOOO MODERVER AVE	-1/// 000	·	<u> </u>
County MULTNOMAH Owner's number, if any	Briler test 025 gal./min. with 13 ft. drawdow	n after	6 hrs.
14 . 14 Section 3 & 4 T. IN R. 1E W.M.	Artesian flow g.p.m. Date	····	
Bearing and distance from section or subdivision corner	Temperature of water 580 Was a chemical analysis m	ade? 🔲 Y	es 🗌 No
Double and about on books of paparished collect	(10)	70 11	
	(12) WELL LOG: Diameter of well	12 "	inches.
	Depth drilled 175 ft. Depth of completed w	rell 1	(5 ft.
	Formation: Describe by color, character, size of materi	al and stru	cture, and
Y	show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each of	the mater hange of	formation.
	MATERIAL	FROM	то
MADE OF MODIC (shorts).			
TYPE OF WORK (check):	Top soil	0	12
New Well		2	63
If abandonment, describe material and procedure in Item 11.	Sand water	63	64.
PROPOSED USE (check): (5) TYPE OF WELL:	Clay & Grey Bilt	64	109
	Sand water	109	125
mestic T Industrial Municipal Rotary Driven Cable Jetted	Gravel w/water (bad oder)	125	751
Irrigation Test Well Other Dug Bored	Coarse Sand & small Gravel		
	water bearing good supply	7 [].	168
(6) CASING INSTALLED: Threaded Welded X		154	100
12 " Diam. from 0 ft. to 175 ft. Gage 5/16	Cemented gravel	168_	175
			ļ
	-	 	
(7) PERFORATIONS: Perforated? T Yes I No	4.		<u> </u>
Type of perforator used Stap It way drive down	WATER CRYSTAL CLEAR AND		
SIZE of perforations 71 in. by 2/8 in.	SAND FREE		
210 perforations from 161 ft. to 171 ft.	The first section of the page]	
perforations from ft. to ft.			
perforations from			
perforations from		 	
perforations from ft. to ft.			
SCREENS: Well screen installed Yes X No		ļ	
Manufacturer's Name			
Type Model No			ļ
Slot size ft. to ft.	-2.50		<u> </u>
Slot size Set from ft, to ft.	Work started JAN-18 19 62 Completed F	3b 21	19 62
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? 🗌 Yes 🛣 No Size of gravel:	Manufacturer's Name		
Gravel placed from ft. to ft.	1_	H.P.	-
Was a surface seal provided? 🙀 Yes 🗌 No To what depth?			***************************************
Material used in seal— Sand & cement	Well Driller's Statement:		
Did any strata contain unusable water? 🛺 Yes 📋 No	This well was drilled under my jurisdiction	and this	roport is
Type of water? Sulphum Depth of strata 1251 to 137	true to the best of my knowledge and belief.	ALLA MILE	TCDOLF 19
Method of sealing strata off Drove Casing		~ ~~	
DIONG OSTITE	NAME HAAKON BOTTNER DRILLING		
(10) WATER LEVELS:	I IIIII TO CITONNI OM	ype or prin	.t)
Static level 12 ft. below land surface Date Heb. 27	Address LIJHH N. E. GIIDAN BE	F	
Artesian pressure lbs. per square inch Date		;	
ADD. POI DQUARO HADII DATO	Driller's well number	·	
Log Accepted by:	[Signed] A. Bollines	_	
	[Signed] (Well Driller)	****************	
[Signed] Date, 19	1 375 MARCH C)	62
(Owner)	License No. Date	, 	, 19