WATER WELL REPORT

1M/1-4A1

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE OF OREGON G486

G433 State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	vel BOT	TNER
Name KERNAN TRAILER VILLAGE	Was a pump test made? X Yes No. If yes, by whom	n? DRI	NG.CO.
Address 11339 N. DENVER AVE.	Yield: 375 gal./min. with 32 ft. drawdov	m after	hrs.
PORTLAND OREGON Owner	" 101 " 101 "		<u></u>
(2) LOCATION OF WELL: Mr.F.J.KERNAN	<u> </u>		<u> </u>
	Failer fest 30 gal./min. with 115 ft. drawdow	n after	2 hrs.
	Arresign forms and Tree g.p.m. Date	/20/5	8
74 74 20000	Temperature of water 53 Was a chemical analysis m	ade? 🔲 Y	es 🙀 No
Bearing and distance from section or subdivision corner	(40) 77777 7 7 0 0	70	
	(12) WELL LOG: Diameter of well	~ ~/	
The second secon	Depth drilled 261 ft. Depth of completed v		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of	al and stru the mater	icture, and ial in each
	stratum penetrated, with at least one entry for each	hange of	formation.
	MATERIAL	FROM	TO
TYPE OF WORK (check):	Sand	0	22
New Well Deepening Reconditioning Abandon	Yellow Clay	22	24
If abandonment, describe material and procedure in Item 11.	San	24	115
	Sandy Blue Clay	115	120
30POSED USE (check): (5) TYPE OF WELL:	Cemented Gravel	120	142
mestic Industrial Municipal Rotary Driven Cable I Jetted	Sand	142	147
Irrigation Test Well Other Dug Bored	Sand & Gravel	147_	185
	Cemented Gravel	185	197
(6) CASING INSTALLED: Threaded Welded	Yellow Water Bearing Sand	197	201
10 "Diam. from	%To much iron & sand)		
ft. Gage ft. Gage	Comented Gravel	201	206
	Sand & Gravel (water) to sand	206	27.0
AND DESCRIPTIONS OF THE PROPERTY OF THE PROPER	Cemented Gravel	210	210
(7) PERFORATIONS: Perforated? No	Gravel (Water Bearing)	246	261
Type of perforator used Star 4 way drive down			
SIZE of perforations 3/8 in. by $1\frac{1}{4}$ in.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations fromft. toft.			
perforations fromft. toft.			
SCREENS: Well screen installed Yes No			
Manufacturer's Name		_	
Type			
Diam. Slot size Set from ft. to ft.	(58)	1	<u> </u>
Slot size Set from ft. to ft.	Work started Jan 23 19 K Completed N	arch	21 19 58
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name		
Gravel placed from ft. to ft.	Type:		
Was a surface seal provided? X Yes \(\simega \) No To what depth? \(\frac{30}{2} \) ft.			
Material used in seal— Sand Gravel & Cement	Well Driller's Statement:		
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Type of water? Depth of strata	true to the best of my knowledge and benef.		
Method of sealing strata off	NAME HAAKON I. BOTTNER DRILL	ING CO) <u>'</u>
(10) WATER LEVELS:	(Person, firm, or corporation) (Type or print)		
Static level 25 ft. below land surface Date 3/12/58	Address		
Artesian pressure lbs. per square inch Date	PORTLAND 20, OREGON Driller's well number		
	Dialet 8 Well Hulliber		
Log Accepted by:	[Signed]		****************
70	(Well Driller)		rfs.
[Signed] Date, 19	License No. 109 Date Dec	4.2	, 1922
	graph and the second property of the second	• • • • • • • • • • • • • • • • • • • •	**