NC

N/1-18

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
OCT 18 1965
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

MULT 987

State Well No. 1N/1E-18

State Permit No.

(1) OWNER:

Name University of Portland

Address 5000 N. Willamette Blvd.
Portland, Ore.

(2) LOCATION OF WELL:

County Multnomah Driller's well number

¼ ¼ Section T. R. W.M.

Bearing and distance from section or subdivision corner
5000 N. Willamette Blvd.
Portland, Ore.

(3) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒

12" Diam. from 13 ft. to 245 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☒ Yes ☐ No

Type of perforator used Mills knife

Size of perforations ½ in. by 2½ in.

336 perforations from 193 ft. to 235 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Bentonite
Depth of seal 40 ft. Was a packer used? No
Diameter of well bore to bottom of seal 16 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 160 ft. below land surface Date 9-30-65
Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom?
Yield: 875 gal./min. with 20 ft. drawdown after 8 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 55° Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing 12"

Depth drilled 247 ft. Depth of completed well 247 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Basement	0	13
Cemented gravel	13	48
Brown sand	48	136
Gravel	136	182
Coarse sand	182	187
Sand & gravel (water bearing)	187	236
Cemented gravel	236	247

Work started 9-10 19 65 Completed 9-30 19 65
Date well drilling machine moved off of well 10-5 19 65

(13) PUMP:

Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME A.M. JANNSEN DRILLING CO.
(Person, firm or corporation) (Type or print)
Address 21075 S.W. Tualatin Hiway
Aloha, Ore.

Drilling Machine Operator's License No. 236 & 274

[Signed] Edwin D. Jannsen
(Water Well Contractor)

Contractor's License No. 79 Date 10-8, 1965

(USE ADDITIONAL SHEETS IF NECESSARY)