NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, REGER SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

SEP 1 40 37 Ovrite above this line

s s

State Well No. 653w-32

SP*45656-119

State Permit No.

WATER RESOURCES DE	TANK TO GA MICAY OF THE T	
(1) OWNER:	(10) LOCATION OF WELL:	ham
Name Chas aucy	County PO/K Driller's well number 14 14 Section 3 2 T. h S R. 3W W.M.	
Address 4 / 5 / Off / Of	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Bearing and distance from Section of Savary	
New Well Deepening □ Reconditioning □ Abandon □	a .	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 175 ft.	
Rotary Driven Domestic Mindustrial Municipal D	Static level 73' ft. below land surface. Date Acy 14, 79	
C Jetted Irrigation Test Well Other	Artesian pressure lbs. per squar	re inch. Date
(5) CASING INSTALLED: Threaded Welded 50	(12) WELL LOG: Diameter of well below casing 6	
"Diam. from ft. to ft. Gage	Depth drilled / 55 ft. Depth of completed well / 55 ft.	
Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
(6) PERFORATIONS: Perforated? Yes You	position of Static Water Level and indicate prin	ncipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	brown clay	0 35
perforations fromft. toft.	sandy brown clay	35' 55
perforations fromft. toft.	sandy gray clay	55 65
(7) SCREENS: Well screen installed? Yes	Sandaray	65 76'
Type Model No.		3/15/
Diam. Slot size Set from ft. to ft. to ft.	Sandy Stoy Clay	/6 /-5
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	green clay	95 16
a pump test made? Yes No If yes, by whom?	green sankstone	104 150
ald: gal./min. with ft. drawdown after hrs.	Constant	150 172
и и и	decomposed rock gray	
<i>n n</i>	elecom posed rock brow	N72 194
power test 25 gal./min. with 97ft. drawdown after hrs.		
sian flow g.p.m.	broken rock	1192/195
Temperature of water Depth artesian flow encountered ft.	Work started Hear 19 75 Comple	ted #4 c/4 19 /
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Hay 14 19 19
Well seal-Material used cement grout	Drilling Machine Operator's Certification	
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] Date	
How was cement grout placed?	Drilling Machine Operator's License No.	
V V /	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used Wes II No Dives Circulacation #	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes \(\subseteq No Plugs	Name EOLA WELL DRILLING (Person, A.P. & Copenion). W. (Type or print)	
Type of water? depth of strata	Address SALEM, OR 97304'	
Method of sealing strata off	Hant X Ron At	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Con	tractor)
Gravel placed from ft. to ft.	Contractor's License No. 4/9 Date	, 19

(USE ADDITIONAL SHEETS IF NECESSARY)