NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON MAY 2 1974 State Well No. 65/3W-20

(Please type or print) STATE ENGINFFP (Please type or print) STATE ENGINEER State Permit No. ...
(Do not write above this ligALEM, OREGON

(1) OWNER: WALLER V	(10) LOCATION OF WELL: County O LK Driller's well number Marsy # 2
Name / / / / / / / / / / / / / / / / / / /	15 3.1
Address 7 4 7	The state of the s
(a) THEN OF WORK (shock).	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	<u>-\frac{1}{2}</u>
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /1 ft.
Rotary Deriven Domestic Industrial Municipal	Static level /2 ft. below land surface. Date 4-/9-7
Cable Jetted Domestic Manager Well Other	484
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 250	Depth drilled 3 ft. Depth of completed well 3 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used ToRC H	MATERIAL From To SWL
Size of perforations in. by in.	Tot Sols 1 0 2 -
// y perforations from 30 ft. to 36 ft.	1380 WN SILT WBrown 2
perforations from it. to it.	(10am) 18 12
perforations fromft. toft.	
perforations fromft. toft.	MRAVELT Buscidet 1/1 20 12
(7) SCREENS: Well screen installed? Yes I No	NI IVITER CONTEST OF THE CONTEST OF
Manufacturer's Name	YKAVEL-MEDGRSG21 38 12
Type Model No.	A DV
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
The state of the s	
Yield: gal./min. with ft. drawdown after hrs.	A STATE OF THE STA
" " " "	Maria de Caracteria de Caracte
" " "	The state of the s
Bailer test 50 gal./min. with 10 ft. drawdown after hrs.	
Artesian flow g.p.m.	
Emperature of water Depth artesian flow encountered ft.	Work started 4 8 19 /4 Completed 4 -/ 9 19 /4
appearance of waters	Date well drilling machine moved off of well 4-19 1974
(9) CONSTRUCTION	
Well seal-Material used Cycly	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface toft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] / tal Date 4-30, 18 4
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my/knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name TODDS NRILLING DEKVICE
Did any strata contain unusable water? Yes You	(Type or print)
Type of water? depth of strata	Address Address Address Address
	1 V-Todd
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 450 Date 4-30 1975
Claused and Enough #t to TI	I WULLDOWN D ALLOUAND BITT PARTIES TO THE TOTAL OF THE TO