

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with:

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED WATER WELL REPORT

STATE OF OREGON

(Please type or print)

State Well No. 65/3W-29

State Permit No. _____

JAN 4 1979

WATER RESOURCES DEPT.

(1) OWNER:

SALEM, OREGON

Name ~~XXXX~~ Robert Hines

Address 6005 Wallase RD. NW

Salem, Oregon 97304

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven
Cable Jetted
Dug Bored

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded

10" Diam. from top ft. to 125 ft. Gage 250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Mills Knife

Size of perforations 3/8 in. by 2 1/2 in.

416 perforations from 83 ft. to 116 ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? driller

Yield: 210 gal./min. with 39 ft. drawdown after 3 hrs.

" " " "

" " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement

Well sealed from land surface to 19 ft.

Diameter of well bore to bottom of seal 14 in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal 12 sacks

How was cement grout placed? poured in from the top

Was a drive shoe used? Yes No Plugs Size: location ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Polk

Driller's well number 2186

1/4 1/4 Section 29 T. 6S R. 3W 3W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 74 ft.

Static level 58 ft. below land surface. Date 10/31/78

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 138 ft. Depth of completed well 125 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown Clay	2	41	
Gray Clay	41	74	
Cemented Black Sand and Gravel	74	116	
Blue Clay	116	138	

Work started 10/26/78 19 Completed 10/31/78 19

Date well drilling machine moved off of well 10/31/78 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Dallas J. Davis Date 10/31/78
(Drilling Machine Operator)

Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 1450 Barnick Rd. NE Salem, OR 97303

[Signed] Dallas J. Davis
(Water Well Contractor)

Contractor's License No. 561 Date 10/31/78, 19