

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED
MAY 13 1972

STATE ENGINEER WATER WELL REPORT
STATE OF OREGON

Polk
9116

State Well No.

6/3W-29 66

State Permit No.

STATE ENGINEER, SALEM, OREGON
within 30 days from the date of well completion.

(Type or print)

SALEM, OR. (Do not write above this line)

(1) OWNER

Name Paul Richenow
Address 805 Fairview Ave SE, Salem, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
6-5/8" O.D. Diam. from 0 ft. to 54 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Type of perforator used Torch Perforated? Yes No.
Size of perforations 7 in. by 6 in.
9.5 perforations from 47 ft. to 52 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " " " "
" " " " " " " "
Baller test 50 gal./min. with 16 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 53° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement & Sand
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Polk Driller's well number
NW 1/4 NW 1/4 Section 29 T. 6S R. 3W W.M.
Bearing and distance from section or subdivision corner
Old Lincoln townsite.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 22 ft.
Static level 22 ft. below land surface. Date 4/24/72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 54 ft. Depth of completed well 54 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	5	-
Willamette Silt	5	12	-
Gravel - Dry	12	17	-
SAND - BROWN - FINE	14	22	22
MRAVEL-MED-			
MULTI COLORS	22	53	22
CLAY-BROWN	53	54	22

Work started 7/16 19 72 Completed 4/24 19 72
Date well drilling machine moved off of well 4/24 19 72

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] A. V. Todd Date 4/1, 19 72
(Drilling Machine Operator)
Drilling Machine Operator's License No. 4/5-1

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Todd's Drilling Service
(Person, firm or corporation) (Type or print)
Address Rt 1 Box 144 Monmouth, Ore
[Signed] A. V. Todd
(Water Well Contractor)
Contractor's License No. 450 Date 3/1, 19 72