## NOTICE TO WATER WELL CONTRACTOR

The original and first copy

The original and first copy of this report are to be filled with the

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 JAN 1 0 1967. (Please type or print) within 30 days from the date of well completion.

STATE ENGINEER, SALEM, OREGON 97310 JAN 1 0 1967. (Please type or print) (Do not write above this line)

State Permit No.

POIK tstate Well No. 6/4w-25addd

SALEM OR CAL	(75130
(1) OWNER:	(11) LOCATION OF WELL:
Name GROWN MALKER	County polk Driller's well number
Address 27 1-130x 752 (6/15mm)	14 14 Section 25 T. ( S R. 4 2 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
No. of the last of	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐  If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing
Cable Z Jetted   Domestic   Industrial   Municipal	Depth drilled 200 ft. Depth of completed well 50 ft.
Dug	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded Welded 2.2. Welded 2.2. tt. to 18 tt. Gage 2.2.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates
"Diam. fromft. Gage	MATERIAL From To SWL
" Diam. from ft. to ft. Gage	COARSIT GRAVAL + 91 118
PERFORATIONS: Perforated? Yes   No.	Blows CLAV
Type of perforator used	BLACK - BASALT 1/8/119
Size of perforations in. by j in.	MARO LADER OF ROCK
perforations from ft. to ft.	BASGAMIASKO-BASA) + 119 158
200 perforations from 75° tt. to 95° tt.	BRAND RED + BLACK
perforations fromft. toft.	- IN COLOR
perforations fromft. toft.	BROWN - CLAY STOKE 15-8 170
perforations from ft. to ft.	- (Magy Sticky)
	13/00 - CTRAY - SEDIMENT 170 200
(7) SCREENS: Well screen installed?   Yes PNo	Pack May
Manufacturer's Name	Miles west = Ville
Type Model No.	1 1 / by 10 10 10 10 10 10 10 10 10 10 10 10 10
Diam. Slot size Set from ft. to ft.	AND OF PARILE AT 1 PT
Diam. Slot size Set from ft. to ft.	- 1211 at Co 3/NO-11 /15 F/
(8) WATER LEVEL: Completed well.	
Static level 26 ft. below land surface Date 10-15-6	
esian pressure lbs. per square inch Date	AND STATE OF THE S
(9) WELL TESTS: Drawdown is amount water level is	
lowered below static level	
Was a pump test made? See No If yes, by whom?	
yield: 75 gal./min. with 92 ft. drawdown after 3 hrs.	Work started 6-3- 1968 Completed 6-15 1968
" "	Date well drilling machine moved off of well /1 - 24 1968
H H H	Drilling Machine Operator's Certification:
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information representations.
Artesian flow g.p.m. Date	rials used and information reported above are true to my best knowledge and belief.
Temperature of water Was a chemical analysis made?   Yes	[Signed] Million West Date 15 16 10/8
(10) CONSTRUCTION:	(Drilling Machine Operator)
Well seal—Material used	Drilling Machine Operator's License No
Depth of sealft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off?   Yes No Depth	true to the best of my knowledge and belief.
Was a drive shoe used?  Yes  No	NAME PHILIPPER - RUBINISON + WEST
Did any strata contain unusable water?   Yes   No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address SEFS VOSE AND ST. O. E. SALEM
Method of sealing strata off	Mail and on
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 37 Date 11-16-1968