NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED OCT 15 1964

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

Polk

State Well No. 6/4W-36

V2264 State Permit No. .....

(1) OWNER:

Name Gordon W alker

Address Route 1, Box 752
Salem, Oregon

(2) LOCATION OF WELL:

County Polk Driller's well number

¼ ¼ Section 36 T. 6 S R. 4 W W.M.

Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒

..." Diam. from ... ft. to ... ft. Gage 14

12" Diam. from 1 ft. above ground level to

..." Diam. from 86 ft. below ground level

(7) PERFORATIONS: Perforated? ☒ Yes ☐ No

Type of perforator used Cutting torch

Size of perforations 3/8 in. by in. 8"

... perforations from ... ft. to ... ft.

60 perforations from 60 ft. to 85 ft.

... perforations from ... ft. to ... ft.

... perforations from ... ft. to ... ft.

... perforations from ... ft. to ... ft.

(8) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name ...

Type ... Model No. ...

Diam. ... Slot size ... Set from ... ft. to ... ft.

Diam. ... Slot size ... Set from ... ft. to ... ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Heavy clay & Bentonite

Depth of seal 18 ft. Was a packer used? ...

Diameter of well bore to bottom of seal 16 in.

Were any loose strata cemented off? ☐ Yes ☒ No Depth ...

Was a drive shoe used? ☒ Yes ☐ No

Was well gravel packed? ☒ Yes ☐ No Size of gravel: #2 round

Gravel placed from 18 ft. to 86 ft.

Did any strata contain unusuable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

(10) WATER LEVELS:

Static level 34 ft. below land surface Date 9/10/64

Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Stettler

Yield: 120 gal./min. with ft. drawdown after hrs.

" " " " " "

" " " " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 48° Was a chemical analysis made? ☐ Yes ☐ No

(12) WELL LOG: Diameter of well below casing 10"

Depth drilled 108 ft. Depth of completed well 108 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Top soil	0	4'
Blue shale	4'	78'
Sand & gravel - large wa ter bearing	78'	85'
Blue clay	85'	100'
Brown clay	100'	108'

Work started Sept. 10, 1964. Completed Sept. 15 1964

Date well drilling machine moved off of well 16 1964

(13) PUMP:

Manufacturer's Name ...

Type: ... H.P. ...

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME ART CLINTON WELL DRILLING CO.
(Person, firm or corporation) (Type or print)

Address Rt. 1, Box 2, Independence, Oregon 97351

Drilling Machine Operator's License No. 34

[Signed] Art Clinton
(Water Well Contractor)

Contractor's License No. 14 Date Sept., 16, 1964

(USE ADDITIONAL SHEETS IF NECESSARY)