The original and first for CE VE WATER WELL REPORT of this report are to filed with the

STATE ENGINEER, SALEM, OREGON 97310

STATE ENGINEER, SALEM, OREGON 97310

WHITE WELL REPOR

STATE OF OREGON

DEPTPlease type or print)

On not write above this line)

SALEM, OREGON



State Well No. 25/3w-30 State Permit No.

SALLINI				
(1) OWNER:	(10) LOCATIÓN OF WELL:			
Name Major Anderson	County Polk Driller's well nu	ımber		
Address 3505 Salem Dallas Hwy N.W.	sw ¼ ne ¼ Section 30 T. 7s	R. 3w	,	W.M.
Salem, Oregon 97304	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):	3505 Salem Dalas Hwy.			
New Well 🛣 Deepening 🗌 Reconditioning 🔲 Abandon 🗌				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	66		ft.
Rotary Driven Domestic Industrial Municipal	Static level 26 ft. below land surface. Date 5/25/75			
Cable 1 Jetted Irrigation Test Well Other	Artesian pressure lbs. per squar	re inch. D	ate	
CASING INSTALLED: Threaded □ Welded ★ # Diam. from +1 ft. to 111 ft. Gage .250 ft. to ft. Gage	(12) WELL LOG: Diameter of well 1 Depth drilled 122 ft. Depth of complete		ng 122	
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forma	m and aqu tion. Repor	iifer pe rt each	enetrated, change in
PERFORATIONS: Perforated? X Yes \(\square\) No. Type of perforator used Mills Knife	position of Static Water Level and indicate prin	From	r-bearing	ng strata. SWL
	goil brown	1	5	
Size of perforations 1/4 in. by 2 in. 126 perforations from 67 ft. to 77 ft.	clay gray	5	37	
126 perforations from 81 ft. to 91 ft.	clay blueish gray	37	66	
perforations from O.L. ft. to J. ft. perforations from ft. to ft.	claystone gray med hard	66	78	26
perforations fromit. toit.	claystone green	78	80	
(7) SCREENS: Well screen installed? Yes No	claystone gray med hard	80	92	26
Manufacturer's Name	clay gray	92	105	
Type Model No	claystone dk gray very hard		121	
Diam Slot size Set from ft. to ft.	sand medium coarse	122		26
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes X No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
				ļ
Bailer test 35 gal./min. with 40 ft. drawdown after 1½ hrs.		1		
Artesian flow g.p.m. Superature of water 54 Depth artesian flow encountered	Work started 5/20 19 75 Complete	ted 6/5		1975
				₁₉ 7 5
(9) CONSTRUCTION:	Drilling Machine Operator's Certification	•		
Well seal—Material used neat cement Well sealed from land surface to	This well was constructed under my Materials used and information reported best knowledge and belief.	direct	supe: ire tru	rvision e to m
Diameter of well bore below seal	[Signed] Paul Bello	Date 6	/20	, 19.75
Number of sacks of cement used in well seal sacks	Drilling Machine Operator) Drilling Machine Operator's License No			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	diction an	d this	report i
of waterlbs./100 gals.	true to the best of my knowledge and belief.			
Was a drive shoe used? M Yes No Plugs Size: location ft.	Name BELLO, WELL DRILLING		ne or **	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) Address 4783 Coloma dr S.E.		pe or pr)re.	
Type of water? depth of strata	Address 4763 Colona ul 5.2.			
Method of sealing strata off	[Signed] Jan Bullo			
Was well gravel packed? ☐ Yes X No Size of gravel:	(Water Well Con			ń:
Gravel placed from ft. to ft.	Contractor's License No. 579 Date	0/20		, 19.75