NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print) (Do not write above this line)

State Well No. 25

(1) OWNER:	(10) LOCATION OF WELL:	
Name UIRGIL PADE	County POLK Driller's well number	
Address 2820 BRUSH COLLEGE RD,	4 14 Section 5 T. 75 R. 3 W.M.	
SACON, ORE 97304	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon A		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 117 ft.	
Rotary Driven Domestic Municipal Domestic Municipal Domestic	Static level 103 ft. below land surface. Date 4-23-	79
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below caring 8"	•
8 " Diam from # ft. to 38 ft. Gage 7	Diameter of well below cashing	
Diam. fromft. toft. Gage	Depth drilled 23/ ft. Depth of completed well 23/ ft.	•
ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
	with at least one entry for each change of formation. Report each change in	<b>1</b>
(6) PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal water-bearing strata.	•
Type of perforator used	MATERIAL From To SWL	<b>.</b> .
Size of perforations in. by in.	top 301C 0 2	æ ·
perforations from ft. to ft.	1305, WEATH, 2 27	
perforations from ft. to ft.	" BROKEN 27 24	-
perforations from ft. to ft.	" POECUS RED 209/11/ 124 103	-
(7) SCREENS: Well screen installed?   Yes No		
Manufacturer's Name	" SEMMY 124 195 " OFXISE 145 221	•
Type	4 BRIKEW 130 g/m 221 231 103	
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED &	
s a pump test made? Yes \( \Bar{\pi}\) No If yes, by whom? SUCED	SEP 2 8 1979 ==	,
rield: 450 gal./min. with 1997ft. drawdown after 3 hrs.		<b>-</b>
" 100 " 83 " 3 "	WATER RESOURCES DEPT	<del>-</del> -
" " "	SALEM, OREGON	
Teiler test gal./min. with ft. drawdown after hrs.		
Temperature of water 48 Depth artesian flow encountered	Work started 9-11 19 79 Completed 9-21 19 79	- 9
remperature of water 78 beptir artesian now encountered	0-21-36	i S
(9) CONSTRUCTION:	Date well drilling machine moved off of well	-
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	y
Diameter of well bore to bottom of seal in.	best knowledge and belief.	>
Diameter of well bore below seal	[Signed] Date 9-27, 1979	•
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	
How was cement grout placed?		-
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	3
Was a drive shoe used? ☐ Yes KNo Plugs Size: location ft.	true to the best of my knowledge and belief.  Name R-7. SNCED WELL DRILLING	
Did any strata contain unusable water?   Yes M No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 4750 ELIZABETH SALEN ORG	· -
Method of sealing strata off	B & S and	
Was well gravel packed? ☐ Yes XNo Size of gravel:	[Signed] (Water Well Contractor)	
Cravel placed from ft to ft	Contractor's License No. 6 Date 9. 27 1975	7