## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.



(Please type or print) STATE ENGINEER State Permit No. .. (Do not write above this inSALEM, OREGON

· · · · · · · · · · · · · · · · · · ·				
(1) OWNER:	(10) LOCATION OF WELL:			
Name Frank Setneker	County Folk Driller's well number			
Address 264 217H				
Me Minnstelles Nove 97/28	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon Reconditioning				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 39, ft.			
Rotary Driven Domestic Industrial Municipal Domestic	Static level $34$ ft. below land surface. Date $7/23/7$			
Dug	Artesian pressure Ibs. per squar	e inch.	Date	
(5) CASING INSTALLED: Threaded   Welded   250   ft. to 20   ft. Gage   250	(12) WELL LOG: Diameter of well below casing			
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;			
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratus	n and a	quifer per	netrated,
PERFORATIONS: Berforated? Yes I No.	with at least one entry for each change of forma position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations 38 in. by 32 in.	Berwa Clay	0	34	
10 6 perforations from 50 ft. to 54 ft.	Barry Clay		39	
perforations from ft. to ft.	Brown Plant & Grond	34	39	·
perforations from ft. to ft.				
	Grown Land.	39	41	
(7) SCREENS: Well screen installed?   Yes No				
Manufacturer's Name	Clay & Growel	4/_	47	
Type Model No, ft. to ft.	the super to the	10	54	
Diam. Slot size Set from ft. to ft.	January June	7/	24	
	Hey Shelo	50	70	<del></del> :
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				-
Was a pump test made?    Yes □ No If yes, by whom?				
Yand: 27 gal./min. with // ft. drawdown after / hrs.		<u> </u>		
" " " " " " " " " " " " " " " " " " " "	,	ļ		<del></del>
" " " "		<del>                                     </del>		<del></del>
Bailer test gal./min. with ft. drawdown after hrs.	The state of the s	<del>                                     </del>		
Artesian flow g.p.m.		<del>                                     </del>		
perature of water Depth artesian flow encountered ft.	Work started 7/9 19 23 Complet	$\frac{1}{\text{ed}} \frac{2}{2}$	23	19 20
	Date well drilling machine moved off of well	2/2	5	19 75
(9) CONSTRUCTION:		110		
Well seal-Material used Bentonito 4/4 Chrush	Drilling Machine Operator's Certification: This well was constructed under my		t gunar	wigion
Well sealed from land surface toft.	Materials used and information reported			
Diameter of well bore to bottom of seal in.	best knowledge and belief.	INS.	7/3	175
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)			
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 453.			
Number of sacks of bentonite used in well seal sacks  Brand name of bentonite				•
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name ROBINSON'S EOLA WELL DRILLING			
Did any strata contain unusable water?   Yes   No	(Person, firm ron corporation D., N. W. (Type or print)			
Type of water? depth of strata	Address SALEM, OREGON 97304			
Method of sealing strata off	[Signed] Heng Ol Roluson			
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)			
Gravel flaced from ft. to ft.	Contractor's License No Date	Z-3	<u>/</u>	, 19