NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
SEP 12 1975
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Polk 172

State Well No. 7S/5W-18
State Permit No.

(1) OWNER:
Name Richard Vorderstrasse
Address Route 2, Box 294-A
Dallas, Oregon 97338

(2) TYPE OF WORK (check):
New Well XXX Deepening XX Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary XXX Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic XXX Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded XXX
..." Diam. from ... ft. to ... ft. Gage ...
6" Diam. from 14 ft. to 19 ft. Gage 1/4"
..." Diam. from ... ft. to ... ft. Gage ...

PERFORATIONS: Perforated? ☐ Yes XX No.
Type of perforator used
Size of perforations in. by in.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.

(7) SCREENS: Well screen installed? ☐ Yes XX No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes XX No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 5 gal./min. with 71 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Heavy clay
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 9" in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal -0- sacks
Number of sacks of bentonite used in well seal -0- sacks
Brand name of bentonite -0-
Number of pounds of bentonite per 100 gallons of water -0- lbs./100 gals.
Was a drive shoe used? XX Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes XX No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes XX No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Polk Driller's well number
¼ ¼ Section 18 T. 7S R. 5W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 54 ft.
Static level 27 ft. below land surface. Date 7-29-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 103 ft. Depth of completed well 103 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top soil	0	1½'	
Brown Clay	1½'	14'	
Blue shale	14'	63'	
Black bedrock (water bearing)	63'	103'	

Work started 7-25-75 19 Completed 7-31-75 19
Date well drilling machine moved off of well 8-1-75 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Art Clinton (Drilling Machine Operator) Date 9-9-75, 19
Drilling Machine Operator's License No. 34

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name ART CLINTON WELL DRILLING Co. (Person, firm or corporation) (Type or print)
Address Rt. 1, Box 2, Independence, Oregon 97351
[Signed] Art Clinton (Water Well Contractor)
Contractor's License No. 14 Date 9-9-75, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119