RACTOR MAY 2 6 1966 WATER WELL REPORT

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the STATE ENGINEER, SALEM, OREGON 97810
STATE ENGINEER, SALEM, OREGON 97810
Within 30 days from the date ALEM OREGON
of well completion.

(Please type or print)

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount volume to lowered below static levels.	vel	
Name Frank Chasteen	Was a pump test made? XYes ☐ No If yes, by whom	, Stet	tler
Address 194 Independence Rd. S.W.	Yield: 380 gal./min. with 25 ft. drawdow	n after	3 hrs.
Salem, Oregon	n n n		
(2) LOCATION OF WELL:	" "		
County Polk Driller's well number	Bailer test gal./min. with ft. drawdo	wn after	hrs.
14 % Section SE 34 T. 7, S R. 4, W W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis n		
	(12) WELL LOG: Diameter of well below case	sing	2
4	Depth drilled 75 ft. Depth of completed well	ı 7	'5 ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each cl	l and struc he materic hange of f	ture, and il in each formation.

(3) TYPE OF WORK (check):	MATERIAL	FROM	то
· · ·	Soil	0	2
New Well X Deepening ☐ Reconditioning ☐ Abandon ☐	Clay - Brown	2	35
abandonment, describe material and procedure in Item 12.	Clay - Blue	35	64_
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Fine to Medium - Sand and Gravel	 	
Domestic Industrial Municipal Rotary Driven	- Brown	++	
Irrigation ★ Test Well Other Dug Bored	Clay Stone - Blue	64	75
(6) CASING INSTALLED: Threaded Welded			
12" Diam. from+1 ft. to65 ft. Gage250			
"Diam. fromft, toft. Gage	Attabase		
(7) DEDEODARIONS.			·
(7) PERFORATIONS: Perforated? ▼ Yes □ No		-	
Type of perforator used Mills Perforator		1	
Size of perforations in. by 3 in.	·		
450 perforations from42 ft. to64 ft.		+ +	
perforations from ft. to ft.		-	
perforations fromft. toft.			
perforations fromft. toft.		 	
perforations from ft. to ft.		1	
(8) SCREENS: Well screen installed? ☐ Yes 🖫 No			
Manufacturer's Name			
n. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.	Work started 4-22-669 Completed	4-28-	
	Date well drilling machine moved off of well	25 ⊷ 66	19
(9) CONSTRUCTION:	(13) PUMP:		
Well seal-Material used in seal Drilling Mud & Bentonite	Manufacturer's Name		
Depth of seal30 ft. Was a packer used?No	Type:		
Diameter of well bore to bottom of seal in. Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? X Yes ☐ No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		TOPOLO I
Gravel placed from ft. to ft.	NAME		
Did any strata contain unusable water? ☐ Yes ☐ No	NAME		
Type of water? depth of strata	Address5545JosephStS.ESalem,Oregon		
Method of sealing strata off	TO		
(10) WATER LEVELS:	,		
21	[Signed] Adamban F. Miffeld (Water Well Contractor)		
State level P. Liv Selovi Anna Barraco Date			
Artesian pressure lbs. per square inch Date	Contractor's License No. 37. Date 4-29-6	<u>y</u>	, 19