

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT RECEIVED

STATE OF OREGON (Please type or print) 2172

State Well No. 75/4W-35 State Permit No. NOV 12 1976 WATER RESOURCES DEPT.

(1) OWNER: Name Green Villa Farms Address Rt 1 Box 259 Independence

(2) TYPE OF WORK (check): New Well [x] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL: Rotary [] Cable [x] Dug [] Driven [] Jetted [] Bored [] (4) PROPOSED USE (check): Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(6) CASING INSTALLED: 12" Diam. from 1 ft. to 41 ft. Gage 250

(7) PERFORATIONS: Type of perforator used 3/8 Mills Size of perforations 2 3/8 in. by 2 1/2 in. 288 perforations from 26 ft. to 38 ft.

(7) SCREENS: Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Bailer test 50 gal./min. with 0 ft. drawdown after 1 hrs.

(9) CONSTRUCTION: Well seal—Material used Bentonite & 1/4 Crush Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 16 in. Diameter of well bore below seal 12 in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks Brand name of bentonite Black Hills Number of pounds of bentonite per 100 gallons of water 30 lbs./100 gals. Was a drive shoe used? [x] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL: SALEM, OREGON County Polk, Driller's well number 1/4 1/4 Section 35 T. 7S R. 42W. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well. Depth at which water was first found 21 ft. Static level 18 ft. below land surface. Date 10-26-76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12 Depth drilled 41 ft. Depth of completed well 41 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Clay - Brown (0-21), Small to med gravel (21-38), Sand (38-40), Gray Claystone (40-41).

Work started 10-25 1976 Completed 10-25 1976 Date well drilling machine moved off of well 10-26 1976

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] James H. Eola Date 11-5, 1976 (Drilling Machine Operator) License No. 455

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. ROBINSON'S EOLA WELL DRILLING Name (Person, firm, or corporation) 4510 DALLAS RD., N.W. (Type or print) Address SALEM, OREGON, 97304 [Signed] George H. Robinson (Water Well Contractor) Contractor's License No. 13 Date 11-8, 1976