WATER WELL REPORT
STATE OF OREGON

RECEIVED
MAR 9 1983
WATER RESOURCES DEPT.
SALEM, OREGON

Polk 218

State Well No. 8S/4W-19

State Permit No.

PLEASE TYPE or PRINT IN INK

(1) OWNER:

Name Fred Purdy
Address 3639 River Rd South
City Salem State Oregon

(2) TYPE OF WORK (check):

New Well XX Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air XX Driven ☐
Rotary Mud ☐ Dug ☐
[illegible] ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic XX Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:

Steel Threaded XX Plastic Welded ☐ XX

6" Diam. from -1 ft. to 51 ft. Gauge .250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? ☐ Yes XX No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes XX No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes XX No If yes, by whom?
[illegible]d: gal./min. with ft. drawdown after hrs.
" " " "
Air test 0 gal./min. with drill stem at 170 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
[illegible]perature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No XX
Well seal—Material used Cement
Well sealed from land surface to 170 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 20 +1 Yard sacks
How was cement grout placed? Trimming Pipe

Was pump installed? No Type HP Depth ft.
Was a drive shoe used? XX Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes XX No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes XX No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Polk Driller's well number Well # 1
¼ ¼ Section 19 T. 8S R. 4W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: Hoffman Rd
Dallas, Oregon

(11) WATER LEVEL: Completed well.

Depth at which water was first found 36 ft.
Static level 0 ft. below land surface. Date 2-25-83
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"
Depth drilled 170 ft. Depth of completed well 0 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Clay	0	6	
Tan Clay	6	15	
Gray Sticky Clay	15	36	
Small Gravel	36	48	
Gray Claystone	48	91	
Light Gray Sandstone	91	106	
Gray claystone	106	152	
Light Brown Claystone	152	170	0

Work started 1-10 19 83 Completed 2-25 19 83
Date well drilling machine moved off of well 2-25 19 83

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Date, 19

Bonded Water Well Constructor Certification:

Bond (number) Issued by: Surety Company Name

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Miller, West Well Drilling (Person, firm or corporation) (Type or print)
Address 5875 Gaffin Rd. S.E. Salem, Oregon
[Signed] J. D. Mondau
Water Well Constructor
Date 3-7, 19 83

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*45292-690