NOTICE TO WATER WELL CONTRICTOR The original and first of this report are to filed with the AUG 14 1972 STATE OF OREGON (Viscos type or print)

Please type or print)

State Well No. State Permit No. ...

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date to the of well completion.

(Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:	
	County CHEY Driller's well	number
Name Edmund Giesbrecht	34 34 Section 9 T. 88	R. 4w W.M.
Address Hiway 51; Rt 1 Box 269	Bearing and distance from section or subdi-	la la l
Independence, Oregon (2) TYPE OF WORK (check):	Bearing and distance from Section	da
AT THE PARTY OF TH		<u> </u>
New Well Deepening Reconditioning Abandon Grandon Grandon abandon ment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	34 <u>ft.</u>
Rotary Driven Domestic Industrial Municipal Domestic	Static level 19 ft. below land surface. Date 7/15/72	
Cable X Jetted	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 8"	
8 " Diam. from 0 ft. to 55 ft. Gage •250	Depth drilled 55 ft. Depth of completed well 55 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain si	ze and structure of materials;
	and show thickness and nature of each str	atum and aquifer penetrated,
	with at least one entry for each change of for position of Static Water Level and indicate 1	principal water-bearing strata.
Perforated? 4 Yes No.		From To SWL
Type of perforator used torch	MATERIAL	0 2 1 SWD
Size of perforations $\frac{1}{4}$ in. by 6 in.	fop soil	
72 perforations from 34 ft. to 53 ft.	clay	2 26
perforations from ft. to ft.	clay & gravle	26 34
perforations from ft. to ft.	sand	34 42
	sand & gravel	41 52
(7) SCREENS: Well screen installed? Yes No	Blue sandstone	52 55
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
1011012011 302011 303011 202011		
Was a pump test made? ☐ Yes 🎛 No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" "	*	
" " "		
Bailer test 100 gal./min. with 29 ft. drawdown after 1 hrs.		
Artesian flow g.p.m.	Work started 7/12/72 19 Com	npleted 7/15/72 19
mperature of water Depth artesian flow encountered ft.	11022 2002 17 12/ 12	
(9) CONSTRUCTION:	Date well drilling machine moved off of w	,
Well seal—Material usedCement_grout	Drilling Machine Operator's Certificat	ion:
Well sealed from land surface to	This well was constructed under Materials used and information report	my direct supervision.
Diameter of well bore to bottom of seal 12 in.	hest knowledge and belief	
Diameter of well bore to bottom or seal	[Signed] Copyright Leine	Date Aug 9 , 1972
Number of sacks of cement used in well seal	(Drilling Machine Operator)	
Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License	No. IOV
Brand name of bentonite		• .
Number of pounds of bentonite per 100 gallons	White West Constitution -	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.	G The Design Co The	
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) (Type or print)	
	Address 3440 SW 34d; Corva	llis, Oregon
Type of water? depth of strata	11. 1 L	16
Method of sealing strata off	[Signed] (Water Well	Contractor)
Was well gravel packed? Tyes To No Size of gravel:		4
Grevel placed from ft. to ft.	Contractor's License No560 Dat	eAugust 17,/19

ft. to ..

Gravel placed from