

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

FORM 2858

WATER WELL REPORT

STATE OF OREGON

RECEIVED JUN 24 1968

STATE ENGINEER SALEM OREGON

STATE ENGINEER SALEM OREGON

State Well No. 8/4w-9

State Permit No. G-6210

SALEM OREGON

(1) OWNER:

Name Mr. David Knaupp Address Greenwood Rd., Independence, Oregon 97351

(11) LOCATION OF WELL:

County Polk Driller's well number 1/4 Section 9 T. 8S R. 4W W.M.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [X] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X]

12" Diam. from 1 ft. above surface to 45 ft. below land surface

PERFORATIONS:

Perforated? [X] Yes [] No

Type of perforator used Cutting torch Size of perforations 7/8 in. by 9 in. 42 perforations from 3 1/2 ft. to 43 1/2 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 30 ft. below land surface Date 5/11/68 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? Stettler Yield: 80 gal./min. with 23 ft. drawdown after 3 1/2 hrs. Bailer test - 0 - gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 48 degrees Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal-Material used Glay & Bentonite Depth of seal 18 ft. Diameter of well bore to bottom of seal 16 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [X] Yes [] No Size of gravel: Large pea Gravel placed from 18 ft. to 45 ft. gravel

(12) WELL LOG:

Diameter of well below casing 11 1/2

Depth drilled 50 ft. Depth of completed well 50 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Brown Clay, Med. gravel & sand (water bearing), Blue Clay.

Work started May 10, 1968 Completed May 14, 1968

Date well drilling machine moved off of well May 15, 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Art Clinton Date June 6, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 34

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME ART CLINTON WELL DRILLING CO. (Person, firm or corporation) (Type or print)

Address Rt. 1, Box 2, Independence, Oregon 97351

[Signed] Art Clinton (Water Well Contractor)

Contractor's License No. 14 Date June 6, 1968