NOTICE TO WATER WELL CONTRACTOR

The original and first copy NOV 17 1965ATER WELL REPORT filed with the

STATE ENGINEER, SALEM, ORESON 9731E ENGINEER OF OREGON within 30 days from the date SALEM OREGON Please type or print) G-3636

State Well No. 8/4w-18 D

State Permit No. ..

•			
1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water level	is
Name Mr. Donald G. Bisbee	Was a pump test made? Yes \[\] No If yes, by whom		
Address Route 1, Box 331	Yield: 70 gal./min, with 19 ft. drawdow		hrs.
Independence, Oregon	" "		
2) LOCATION OF WELL:	" "		
•	Bailer test gal./min. with ft. drawd	own after	hrs.
County Polk Driller's well number 14 34 Section 9 T. 8 5 R. 4 W W.M.	Artesian flow g.p.m. Date		
14 14 Section 9 T. 6 S R. 4 W.M. Bearing and distance from section or subdivision corner	Temperature of water 480 Was a chemical analysis		
searing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below co	asing12	11
	Depth drilled 15 ft. Depth of completed we	<u>:</u> 11	45 ft.
	1		ture, and
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each of	the materia hange of fo	ormation.
NWNW See 10	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	MAIERIAL	FIGH	
```.	Ton soil	0	1.1
Newell Deepening Reconditioning Abandon Sandon Sandonment, describe material and procedure in Item 12.	Top soil	+ +	
	Brown olaw	), 1	7),1
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown clay	+ 4.	14
Domestic   Industrial   Municipal   Rotary   Driven   Coblo	Sand & gravel - med.	7),1	121
(rrigation K Test Well □ Other □ Dug □ Bored □	(water bearing)		- Corp Corp
	(nauct post tits)	1	
(6) CASING INSTALLED: Threaded Welded 1	XXI	1	
12" Diam. fromft. toft. Gage	Blue shale	L2:	451
"Diam from 16" above ground flevel to	and the term of the term o		
" Diam. from Lill ft. below groundGalevel.			
(7) PERFORATIONS: Perforated? X Yes  No			-
Type of perforator used Gutting torch		ì	
Size of perforations $\frac{1}{4}$ in. by 8 in.			2.44
		1	* : .
		1 1	
perforations from ft. to ft.		1	
perforations from ft. to ft.		<u> </u>	
perforations from ft. to ft.		+	
(8) SCREENS: Well screen installed? ☐ Yes ▼ No		+ +	· · · · · · · · · · · · · · · · · · ·
Manufacturer's Name		+	· · · · · · · · · · · · · · · · · · ·
Model No.			
Diam. Slot size Set from ft. to ft.	W	<del>مام مار</del>	1065
Diam		Oct. 25,	196 <u>5</u>
		Oct. 25.	<u>1965</u>
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Bentonite	Manufacturer's Name		
Depth of seal	Type:	н.р	
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:		
Were any loose strata cemented off? 🗆 Yes 🕻 No Depth	.	=	=
Was a drive shoe used? 🏋 Yes □ No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? Tyes   No Size of gravel:peagrave	true to the best of my knowledge and belief.		
Gravel placed from18ft. to14.	NAME ART CLINTON WELL DRILLIN		
Did any strata contain unusable water? 🔲 Yes 📡 No	(Person, firm or corporation) (T	ype or print)	
Type of water? depth of strata	Address Route 1, Box 2, Independe	noe ore	28711 7
Method of sealing strata off	Drilling Machine Operator's License No34		
(10) WATER LEVELS:	Challo +		
70/00/64	[Signed] (Water Well Contractor	)	·····
Static level 22 ft. below land surface Date 10/22/65	7). Norre	-	65
Artesian pressure lbs. per square inch Date	Contractor's License No. 14 Date Nove		2. 19