## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPO

STATE OF OREGON

(Please type or print) STATE ENGINEER

(Do not write above this line) SALEM. OREGON This No.

(1) OWNER: Y	(10) LOCATION OF WELL:
Name Green Willa Farms	CountyPolk Driller's well number
Address Independance Or.	S.W. 14 Now 14 Section 15 T. 8.S R. 4 W. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 21 ft.
eVRotary Driven Domestic Industrial Municipal	Static level 12 ft. below land surface. Date 6/6/73
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded 1   Welded 2   21   ft. Gage 250	(12) WELL LOG: Diameter of well below casing Depth drilled 4 1 ft. Depth of completed well 41 ft.
ft. toft. Gageft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes  No.	position of Static Water Level and indicate principal water-bearing strata.  MATERIAL From To SWL
Type of perforator used	
Size of perforations in. by in.	Top soil brn. 0 3
perforations from ft. to ft.	Clay sandy brn. 3 17
perforations from ft. to ft.	Med gravel brn. = 17 36 W.B.
perforations from ft. to ft.	Hespale grey- hrn. 40 41
(7) SCREENS: Well screen installed? ¾ Yes □ No	He shale grey-brn. 40 41
Manufacturer's Name  Johnsom	
Type Irrigater Model No. 100	
Diam 8. Slot size 100 Set from 21 ft. to 41 ft.	
Diam. Slot size Set from ft. to ft.	
Diani, Dio size manufactura de la companya de la co	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? A Yes D No If yes, by whom? Driller	5
Yield: 400 gal./min. with 23 ft. drawdown after 5 hrs.	West to the second seco
ried: 100 gar./min. with 20 11. drawdown area 9 ms.	
	The property of the second sec
и и и и	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 6/5 1973 Completed 6/6/73 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/6/73
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to 18 ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal 36 in.	[Signed] Date 6/18/73, 19
Number of sacks of cement used in well seal 3 yds. sacks	Drilling Machine Operator's License No84
Number of sacks of bentonite used in well sealsacks	Drinning Machine Operator's Literase 140.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used?   Yes No Plugs Size: location ft.	Name R. Stadeli& Sons Inc.  (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? 🛘 Yes 🏝 No	" "Silverton-Oreg.
Type of water? depth of strata	Address
Method of sealing strata off	[Signed] Laul T. Stadeli
Was well gravel packed? * Yes 🗆 No Size of gravel: 3/4	(Water Well Contractor)
Gravel placed from the fit to the fit	Contractor's License No. 296 Date 6/18/73 19