NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Polk 2963

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 8S/4W-28
State Permit No.

(1) OWNER:
Name City of Monmouth
Address 151 west Main Street Monmouth Or, 97361

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☒
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☒
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☒
12" Diam. from approx. ft. to 0-60 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☒ Yes ☐ No.
Type of perforator used Unknown
Size of perforations in. by in.
Unknown # perforations from 40 ft. to 60 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom? N/A
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Well previously sealed
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Polk Driller's well number
¼ ¼ Section 28 T. 8S R. 4W W.M.
Bearing and distance from section or subdivision corner
City Well #3

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 39 ft. below land surface. Date 7-2-79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 62
Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Well filled to 37 ft. with #2 Round gravel. A 3 ft. plug was placed from 34-37 ft. Cement plug was mixed and pumped through 1" tremie pipe. Remaineder of hole was filled with 3/4 minus concrete. Casing was cut off 3' below ground level.			

RECEIVED
JUL 26 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 7-2 19 Completed 7-2 19 79
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Vic Todd (Drilling Machine Operator) Date 7-21-1979
Drilling Machine Operator's License No. 1152

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Vic Todd Water Well Drilling (Person, firm or corporation) (Type or print)
Address 523 S.E. 38th Av. Albany, Or. 97321
[Signed] Vic Todd (Water Well Contractor)
Contractor's License No. 678 Date 7-2, 19 79

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119