NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT STATE OF OREGON

(Please type or print)

(Do not write above this line)

State	Well No. 8s /4w-28
State	Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name City of Monmouth	County Polk Driller's well number
Address 151 West Main Street Monmouth Or. 9736	1 34 34 Section 28 T. 88 R. 4W W.M.
(0) MADE OF MODE (-11-).	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	City Well # 2
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ♣	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal V	Static level 39 ft. below land surface. Date 3-279
Cable	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 12 Welded 12 Welded 12 Welded 250 Tt. Gage 250	(12) WELL LOG: Diameter of well below casing 72
" Diam. fromft. toft. Gage	Depth drilled ft. Depth of completed well ft.
" Diam. fromft. Gage	Formation: Describe color, texture, grain size and structure of materials;
Didni Hvii	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? In Yes In No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Unknown	MATERIAL From To SWL
Size of perforations in. by in.	Well filled to 40 ft. with
Unknown # perforations from 45 ft. to 65 ft.	#2 Round gravel, A 3 ft. plug
perforations fromft. toft.	was placed from 37-40 ft.
perforations fromft. toft.	Cement plug was mixed and
	pumped through 1" tremie pipe
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Remainder of hole was filled
Manufacturer's Name	with 3/4 minus concrete.
Type Model No	Casing was cut off 3 below
Diam. Slot size	ground level.
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	57 F 60 P 8 9 P 1 P 1
lowered below static level	TEULIVED -
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	THE CONTRACTOR OF
Yield: gal./min. with ft. drawdown after hrs.	
" " " "	WATER RESOURCES DEPT
<i>"</i> " " " " " " " " " " " " " " " " " "	SALEM, OREGON
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 7-2 19 79 completed 7-2 19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19
Well seal—Material used/ell_previously_sealed	Drilling Machine Operator's Certification:
Well sealed from land surface to ft,	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below sealin.	[Signed] Orilling Machine Operator) Date 7+2-7.9
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
How was cement grout placed?	Diffing Machine Operators Direction 1300
The state of the s	Water Well Contractor's Certification:
· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? IT Vos IT No Diver	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size; location ft. Did any strata contain unusable water? ☐ Yes ☐ No	Name Vic Todd Water Well Drilling (Person, firm or corporation) (Type or print)
	503 S F. 38th Arr / Albant On 07301
Type of water? depth of strata	
Method of sealing strata off	[Signed]
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 67.8 Date 7 2, 19.79