

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

RECEIVED POLK 2969 WATER WELL REPORT NOV 14 1969 STATE OF OREGON STATE ENGINEER SALEM, OREGON

Polk 29189 State Well No. 8/4W-28 State Permit No. G5106

(1) OWNER: City of Monmouth Name Ken Martin, City Manager Address City Hall, Monmouth, Oregon 97361

(2) TYPE OF WORK (check): New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Dug [ ] Bored [ ] (4) PROPOSED USE (check): Domestic [ ] Industrial [ ] Municipal [x] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED: Threaded [ ] Welded [x] 1/2" Diam. from ... ft. to ... ft. Gage 1/4" 12" Diam. from 1 ft. above land surface to ... ft. 62" Diam. from 62 ft. below land surface to ... ft.

PERFORATIONS: Perforated? [x] Yes [ ] No. Type of perforator used Cutting torch Size of perforations 3/8 in. by 8 in. perforations from ... ft. to ... ft. 69 perforations from 40 ft. to 60 ft.

(7) SCREENS: Well screen installed? [ ] Yes [x] No Manufacturer's Name ... Type ... Model No. Diam. Slot size Set from ... ft. to ... ft.

(8) WATER LEVEL: Completed well. Static level 38 ft. below land surface Date ... Artesian pressure lbs. per square inch Date ...

(9) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [ ] No If yes, by whom? Stettler Yield: 280 gal./min. with 16 ft. drawdown after 9 1/2 hrs.

(10) CONSTRUCTION: Well seal—Material used Bentonite & heavy clay Depth of seal 18 ft. Diameter of well bore to bottom of seal 16 in. Were any loose strata cemented off? [ ] Yes [x] No Depth ... Was a drive shoe used? [x] Yes [ ] No Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [ ] No Size of gravel: #2 round Gravel placed from 18 ft. to 62 ft.

(11) LOCATION OF WELL: County Polk Driller's well number 1/4 1/4 Section 28 T. 8S R. 1W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing -0- Depth drilled 62 ft. Depth of completed well 62 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Top soil (0 to 3'), Brown clay (3' to 36'), Brown sandy clay (36' to 40'), Coarse sand & med. gravel (water bearing) (40' to 62').

Work started Oct. 13, 1969 Completed Oct. 16, 1969 Date well drilling machine moved off of well Oct. 20, 1969

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Art Clinton Date 11-12-1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 34

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. NAME ART CLINTON WELL DRILLING CO. (Person, firm or corporation) (Type or print) Address Rt.1, Box 2, Independence, Oregon 97351 [Signed] Art Clinton (Water Well Contractor) Contractor's License No. 14 Date November 12, 1969