NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT ESTATE OF OREGON

PONC State

10 8/4w-28 P

filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date

of well completion.

APR 8 19600 not write above this line)

State Permit No.

STATE ENGINEER	6-4332
1) OWNER: SALEM OREGON	(11) LOCATION OF WELL: City Well # 1
Name City of Monmouth c/o Ken Martin, Mgr.	County Polk Driller's well number
Address Monmouth, Oregon	1/4 1/4 Section 28 T. 8 S R. 4 W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
Yew Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐	· · · · · · · · · · · · · · · · · · ·
f abandonment, describe material and procedure in Item 12.	
Potenty C Driven C	(12) WELL LOG: Diameter of well below casing
Cable Jetted Domestic Industrial Municipal K	Depth drilled 72 ft. Depth of completed well 72 ft.
Oug Bored I Irrigation Test Well Other	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change
" Diam, from ft. to ft. Gage	in position of Static Water Level as drilling proceeds. Note drilling rates.
12" Diam. from 1 n. tabove land, sapeface to	MATERIAL From To SWL
"Diam. from 66 ft. thelow land sageface	
PERFORATIONS: Perforated W Yes No. 14	Top soil 0 21
kti kti	
	Grav clav 21 311
Size of perforations 5/16 in. by 9 in.	<u> </u>
perforations from ft. to ft.	Coarse sand & Med. Grave 311 661 371
80 perforations from 47 ft. to 66 ft.	(water bearing)
perforations from ft. to ft.	
perforations from ft. to ft.	Blue clay 661 721
perforations fromft. toft.	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WATER LEVEL: Completed well.	
2/20/68	* .
an pressure lbs. per square inch Date	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? If Yes D No If yes, by whom? Stettler	
Vield: 270 gal./min. with 261 ft. drawdown after 3 hrs.	Work started 2/28/68 19 Completed 3/7/68 19
200 " 12½ " 1 Hr. hOMin.	Date well drilling machine moved off of well $3/12/68$ 19
" " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification:
	This well was constructed under my direct supervision. Mate-
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported above are true to my best knowledge and belief.
Artesian flow g.p.m. Date	010/14
Temperature of water 50 Was a chemical analysis made? Yes No	[Signed] Lan Cluster Date April 6, 19.68
(10) CONSTRUCTION:	
Well seal-Material used Heavy clay & bentonite	Drilling Machine Operator's License No. 34
Depth of seal 18 ft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of seal16 in.	This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No	NAME ART CLINTON WELL DRILLING CO. (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes I No	Rt. 1 Box 2 Independence Oregon 9735
Type of water? depth of strata	Address 10.1, DOX 2, Independence, Oregon 9755
Method of sealing strata off	[Signed] ark Clinton
Was well gravel packed? N Yes □ No Size of gravel #2 round	(Water Well Contractor)
Gravel placed from18ft. to66ft.	Contractor's License No. 14 Date April 6, 1968

(USE ADDITIONAL SHEETS IF NECESSARY)