

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

WATER WELL REPORT
MAY 27 1958
STATE OF OREGON
STATE ENGINEER

POLK
30301

State Well No. 8/4W-33B
State Permit No.

(1) OWNER: SALEM, OREGON
Name Gordon K. HANSON
Address RT 1 Box 6 Independence Ore

(2) LOCATION OF WELL:
County Polk Owner's number, if any—
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 11.

(4) PROPOSED USE (check):
Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:
Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED: Threaded Welded
0" Diam. from 58 ft. to ft. Gage

(7) PERFORATIONS: Perforated? Yes No
Type of perforator used
SIZE of perforations 1/4 in. by 16 in.
5 perforations from 56 ft. to ft.

(8) SCREENS: Well screen installed Yes No
Manufacturer's Name
Type Model No.
Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.
Was a surface seal provided? Yes No To what depth? ft.
Material used in seal—
Did any strata contain unusable water? Yes No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 30 ft. below land surface Date 5/22/58
Artesian pressure lbs. per square inch Date

Log Accepted by:
[Signed] Date 19

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bailer test 45 gal./min. with 4 ft. drawdown after 2 hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? Yes No

(12) WELL LOG: Diameter of well 6 inches.
Depth drilled 58 ft. Depth of completed well 58 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
soil	0	5
Clay (Brown)	5	32
Cement Gravel	32	40
SAND (black silty)	40	48
SAND (medium brown)	48	54
Gravel (1/2 to 2 in) w/sand	54	58
Coarse Brown		

Work started May 21 1958 Completed May 22 1958

(13) PUMP:
Manufacturer's Name
Type: H.P.

Well Driller's Statement:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Gilbert A. Pruitt
Address RT 4 Box 53 Corvallis
Driller's well number
[Signed] Gilbert A. Pruitt
License No. 23 Date 5/23 1958

Hanson

RECEIVED
MAY 27 1958

V 137

STATE ENGINEER
SALEM, OREGON

Beginning at a point 16.98 chains south of the northeast corner on the East boundry line of Isseal Hedges Donation Land Claim No. 46, in Township 8 South,, Range 4 West of the Willamette Meridian in Polk County, Oregon; at a post which is the Southeast corner of Viola Sloper's land; thence running West ~~14.50 chains~~ ^{14.50 chains} to the East line of the County Road; thence South 8° 30' West 8.23 chains along the East side of said road; thence east 15.56 chains to the East line of said Donation Land Claim; thence North on said line 8.14 chains to the place of beginning, containing 12.39 acres, more or less.