NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

P8/R 3613

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

(Do not write above this line)

RECEIVED
MAY - 4 1977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 8S/6W-17

State Permit No.

(1) OWNER:
Name J.F. Buckovic
Address 778 W. Main, Monmouth

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from 1 above to 37 ft. Gage 250
" Diam. from ft. to ft. Gage
P.V.C. 5" Diam. from 35 ft. to 95 ft. Gage

PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used cutting torch + skil saw
Size of perforations 1/4 in. by 6 in.
10 perforations from 28 ft. to 38 ft.
P.V.C. ~~perforations from~~ 1/8 x 6" ~~ft. to~~ ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 10 gal./min. with 67 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement grout
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 5 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☑ Yes ☐ No Size of gravel: 3/4 minus
Gravel placed from 18 ft. to 36 ft.

(10) LOCATION OF WELL:
County Polk Driller's well number
1/4 1/4 Section 17 T. 8S R. 6W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 24 ft.
Static level 18 ft. below land surface. Date 4-30-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 95 ft. Depth of completed well 95 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top soil	0	3	
Brown clay	3	6	
Grey clay	6	9	
Yellow clay-grey layers	9	36	
Blue claystone	36	41	
Blue claystone-yellow layers	41	59	
Yellow clay	59	70	
Blue sandstone	70	77	
Grey claystone	77	95	

Work started 4-28 1977 Completed 4-30 1977
Date well drilling machine moved off of well 4-30 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Paul Dickerson (Drilling Machine Operator) Date 4-30, 1977
Drilling Machine Operator's License No. 549

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Todd's Drilling Service (Person, firm or corporation) (Type or print)
Address Rt. 1 Box 144, Monmouth
[Signed] C. V. Todd (Water Well Contractor)
Contractor's License No. 450 Date 5-2, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119