

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

3700 POLK WATER WELL REPORT
STATE OF OREGON
(Please type or print)

RECEIVED

AUG 18 1975

State Well No. 95/4W-1
State Permit No.

(Do not write above this line) WATER RESOURCES DEPT.

(1) OWNER:

Name DOUGLAS HADLEY
Address RT 1 BOX 53A
INDEPENDENCE OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
12 3/4" Diam. from 0 ft. to 37 ft. Gage 1.250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used MILLS
Size of perforations 3/8 in. by 2 1/2 in.
288 perforations from 25 ft. to 35 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 50 gal./min. with 10 ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 57 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement & Sand
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 15 1/2 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 4 1/2 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County POLK Driller's well number
NW 1/4 NE 1/4 Section 1 T. 95 R. 4W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 18 ft.
Static level 1.5 ft. below land surface. Date 8-11-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10
Depth drilled 37 ft. Depth of completed well 37 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	2	-
CLAY-BROWN-SILT	2	18	-
GRAVEL-CORSE	18	35	15
CLAY-BLUE-SOFT	35	37	15

Work started 8-7 19 75 Completed 8-11 19 75
Date well drilling machine moved off of well 8-11 19 75

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] C.V. Todd Date 8-16, 19 75
(Drilling Machine Operator)

Drilling Machine Operator's License No. 451

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TODD'S DRILLING SERVICE
(Person, firm or corporation) (Type or print)

Address RT 1 BOX 144, MONMOUTH, ORE.

[Signed] C.V. Todd
(Water Well Contractor)

Contractor's License No. 450 Date 8-16, 19 75