

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED
STATE OF OREGON
(Please type or print)
STATE ENGINEER
SALEM, OREGON

MAY 20 1974

State Well No. 95/4W-14
State Permit No. G6850

(1) OWNER:

Name JAMES HARWOOD
Address RT-1, Box 79
INDEPENDENCE, OREGON

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

123.98" Diam. from +2 ft. to 50 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Type of perforator used TORCH Perforated? Yes No.
Size of perforations 7 in. by 1/2 in.
132 perforations from 40 ft. to 48 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 50 gal./min. with NO ft. drawdown after 2 hrs.
Artesian flow g.p.m.

Temperature of water 54° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement + Sand
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 15 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 7 sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County POLK Driller's well number Journal # 1
NW 1/4 SE 1/4 Section 14 T. 9S R. 4W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 21 ft.
Static level 21 ft. below land surface. Date 5-14-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 58 ft. Depth of completed well 58 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	2	-
BROWN SILTY CLAY	2	18	-
GRAVEL-MED COURSE	18	21	21
GRAVEL-COURSE	21	48	21
GRAVEL-CONSOLIDATED	48	49	21
CLAY-BLUE-SOFT	49	58	21

Work started 5-10 1974 Completed 5-14 1974
Date well drilling machine moved off of well 5-14 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] C.V. Todd Date 5-16, 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 451

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Todd's Drilling Service
(Person, firm or corporation) (Type or print)
Address 157 #1, Box 144-Monmouth, Ore
[Signed] C.V. Todd
(Water Well Contractor)
Contractor's License No. 450 Date 5-16, 1974