NOTICE TO WATER WELL CONTRACTOR MAY 3 1966

The original and first copy MAY 3 1966

of this report are to be filed with the STATE ENGINEER WELL REPORT STATE ENGINEER OF OREGON within 30 days from the date SALEM. OREGON Flease type or print)

3916	١			,		
500	State	Well No.	91	4w-	30	J

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we	ater level is			
Name Mr. Fredric Shildmever	Was a pump test made? Yes No If yes, by whom?				
Address Rt. 1, Box 143, Monmouth, Oregon	Yield: gal./min. with ft. drawdown	_			
, -	" "	"			
(2) LOCATION OF WELL:	" " "	"			
County Polk Driller's well number N66-2	Bailer test 33 gal./min. with 5 ft. drawdow	m after 1 hrs.			
NW 14 NW 14 Section 30 T. 95 R. 4 W W.M.	Artesian flow g.p.m. Date				
Bearing and distance from section or subdivision corner	Temperature of water 53 Was a chemical analysis ma				
	(12) WELL LOG: Diameter of well below casis	ng			
	Depth drilled 175 ft. Depth of completed well	175 ft.			
	Formation: Describe by color, character, size of material a show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each character.				
		nge of formation.			
(3) TYPE OF WORK (check):		FROM TO			
New Well K Deepening ☐ Reconditioning ☐ Abandon ☐	Top Soil	0 4			
andonment, describe material and procedure in Item 12.	Yellow Clay	4 10			
	Blue Sandy Clay Blue Sand Stone	10 26			
(4) PROPOSED USE (check): (5) TYPE OF WELL:		26 36 36 49			
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ Cable ☐ Jetted ☐	Sand Stone	49 175			
Irrigation	30220				
(6) CASING INSTALLED: Threaded Welded					
8 % 8 OD of the 34 the Gage 250					
" Diam. fromft. toft. Gage					
" Diam. from ft. to ft. Gage					
(7) DEDECD ADJONIC.					
rentotated: 1 tes 14 No					
Type of perforator used					
Size of perforations in. by in.					
perforations from ft. to ft					
perforations from ft. to ft.					
perforations from ft. to ft.					
perforations from					
(8) SCREENS: Well screen installed? ☐ Yes ☐ No					
Manufacturer's Name					
Treno					
Model No. Slot size					
Diam Slot size Set from ft. to ft.	Work started 4/11 1966 Completed 4/25				
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4/23	<u>19 6</u> 6			
	(13) PUMP:				
Well seal—Material used in seal Bentonite	Manufacturer's Name None Installed				
Depth of seal 0 to 18 ft. Was a packer used? NO	Type: H.F	>			
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:				
Were any loose strata cemented off? Tyes No Depth					
Was a drive shoe used? [XYes] No	This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	d this report is			
Was well gravel packed? ☐ Ycs K No Size of gravel:					
Gravel placed fromft. toft.	NAME Todd's Drilling Service (Person, firm or corporation) (Type	··································			
Did any strata contain unusable water? 口Yes 耳No Type of water? SOft depth of strata	(Person, firm or corporation) (Type or print) AddressRtlBox1.44Monmouthore.gon				
Method of sealing strata off		380U			
(10) WATER LEVELS:	Drilling Machine Operator's License No. 451				
	[Signed]				
Static level 30 ft. below land surface Date $4/23/66$	[Signed] (Water Well Contractor)				
Artesian pressure lbs. per square inch Date	Contractor's License No. 450 Date 4/27	_{19.} 66			