WATER WELL REPORT

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be, filed with the file state of the within 30 days from the date of well completion. STATE OF OREGON (Please type or print)

within 30 days from the date (Please type of well completion.	pe or print) State Permit No
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Chester Slater	Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Address Rt. 1 Box 156	Yield: gal./min. with ft. drawdown after hrs
Monmouth, Oregon	" " " " " " " " " " " " " " " " " " "
(2) LOCATION OF WELL:	n n n
County POIk Driller's well number N12-66	Bailer test 20 gal./min. with 10 ft. drawdown after 1 hrs
SE 1/4 NW 1/4 Section 32 T. 9S R. 4W W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water 53 Was a chemical analysis made? Tes 53 Was a chemical analysis made?
pouring and distance from bootstate of Basarrasan connec	(12) WELL LOG: Diameter of well below casing
	Depth drilled 44 ft. Depth of completed well 44 ft
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top soil 0 1
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Brown clav $1\frac{1}{2}$ $1\frac{1}{2}$
bandonment, describe material and procedure in Item 12.	Yellow clay 12 18
(4) DDODOGED LIGE (cheek). (5) TVDE OF WELL.	Sandy yellow clay 18 32
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown sænd (fine water-
Domestic K Industrial Municipal Cable X Jetted	bearing) 32 34
Irrigation	Coarse sand and fine gravel 34 44
(6) CASING INSTALLED: Threaded Welded W	(blue water bearing)
.6	
(7) PERFORATIONS: Perforated? ☑ Yes ☐ No	
Type of perforator used torch	
Size of perforations 1/8 in. by 4 in.	
240 perforations from 34 ft. to 44 ft.	
perforations from ft. to ft.	
ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes ₩ No	
Manufacturer's Name	
Model No	
1	Work started 7/9 1966 Completed 7/13 196
$\label{eq:def:Diam.scale} Diam. \dots \\ Slot \ size \ \dots \\ Set \ from \ \dots \\ ft. \ to \ \dots \\ ft.$	Date well drilling machine moved off of well 7/13 196
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal	Manufacturer's Name
Depth of sealft. Was a packer used?	Type: H.P.
Diameter of well bore to bottom of seal	
Were any loose strata cemented off? ☐ Yes 🔀 No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ☐ Yes ∑No	This well was drilled under my jurisdiction and this report is
Was well gravel packed? $\hfill\square$ Yes \hfill No \hfill Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME Todd's Drilling Service (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes K No	
Type of water? depth of strata	Address Rt. 1 Box 144 Monmouth, Oregon
Method of sealing strata off	Drilling Machine Operator's License No. 451
(10) WATER LEVELS:	01/1.11
Static level 13 ft. below land surface Date 7/13/66	[Signed] (Water Well Contractor)
Static level 13 ft. below land surface Date 7/13/66 Artesian pressure lbs. per square inch Date	Contractor's License No. 450 Date 7/25 1956