NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

The state of the second of the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)
(Do not write above this line)

POIK State Well No. 65/3W-29 66 50255 State Permit No.

(10) LOCATION OF WELL: (1) OWNER: Driller's well number Perrydale Water District Polk Name 14 NW 14 Section 29 **T.** 63 Address R. 3W W.M. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning Abandon 🛚 New Well Deepening | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Driven 🗆 Rotary ft. below land surface. Date 8/15 Domestic 🔲 Industrial 🔲 Municipal 🛣 Static level Cable Jetted Irrigation

Test Well

Other Dug Bored 🔲 lbs. per square inch. Date Artesian pressure (5) CASING INSTALLED: Threaded 🔲 Welded 🗷 (12) WELL LOG: Diameter of well below casing10. 10 " Diam from plus 2 ft. to 66 ft. Gage 250 Depth drilled ft. Depth of completed well ." Diam. from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; " Diam. from ft. to ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? | Yes | No. MATERIAL From Type of perforator used silty top soil lt. brown 0 2 Size of perforations in. by clav silt brown 35 perforations from ft. to ft. 35 silt blue 51 perforations from ft. to ft. 59 silty sand black 51 perforations from ft. to 59 67 gravelly sand silty black (7) SCREENS: 11 Well screen installed? Tyes 🔲 No 67 medium samu black 72 Manufacturer's Name Johnson clay sand parent) 72 stainless steel _____ Model No. ____304 Ħ clay sand ; gravel green 73 Diam. 92 Slot size 18 Set from 715 ft. to 642 # clay silt blue 79 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? Z Yes No If yes, by whom? Zent's gal./min. with 42 ft. drawdown after 24 Yield: Bailer test gal./min. with ft, drawdown after Artesian flow 8/15/85 19 Completed 8/29/75Temperature of water Depth artesian flow encountered Work started 19 Date well drilling machine moved off of well September 1 1975 (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used ____CGMent grout This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal ... (Drilling Machine Operator) [Signed] Lie rale 10 in. Diameter of well bore below seal Number of sacks of cement used in well seal _5 sacks/yd Drilling Machine Operator's License No.574...... Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Name Zent Drilling, Inc.
(Type or print) Was a drive shoe used? 🗷 Yes 🔲 No Plugs Size: location ft. Did any strata contain unusable water?

Yes
No 7310 St. Johns Vancouver, Wash. 98665 depth of strata Type of water? Method of sealing strata off (Water Well Contractor) Was well gravel packed? Yes No Size of gravel: Contractor's License No. 228 Date 2/39 ., 19. Gravel placed from ft. to