

JUL 24 1998

Westerberg Drilling, Inc.
36728 S. Kropf Rd.
Molalla, OR 97038
829-2526

STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by ORS 537.765)

WATER RESOURCES DEPT.
WELL I.D. # L 2867 SALEM, OREGON
START CARD # 111442

Instructions for completing this report are on the last page of this form.

(1) OWNER: Well Number
Name WILLAMETTE IND. INC.
Address P.O. BOX 907
City ALBANY State OR Zip 97321

(2) TYPE OF WORK
[X] New Well [ ] Deepening [ ] Alteration (repair/recondition) [ ] Abandonment

(3) DRILL METHOD:
[X] Rotary Air [ ] Rotary Mud [ ] Cable [ ] Auger
[ ] Other

(4) PROPOSED USE:
[X] Domestic [ ] Community [ ] Industrial [ ] Irrigation
[ ] Thermal [ ] Injection [ ] Livestock [ ] Other

(5) BORE HOLE CONSTRUCTION:
Special Construction approval [ ] Yes [X] No Depth of Completed Well 426 ft.
Explosives used [ ] Yes [X] No Type Amount

Table with columns: HOLE, SEAL, Diameter, From, To, Material, Sacks or pounds. Rows include BENT, CEMENT, CEMENT with various diameters and quantities.

How was seal placed: Method [ ] A [X] B [X] C [ ] D [ ] E
[X] Other BENT PLACED DRY
Backfill placed from 426 ft. to 435 ft. Material HOLE SLOUGH
Gravel placed from ft. to ft. Size of gravel

(6) CASING/LINER: Table with columns: Diameter, From, To, Gauge, Steel, Plastic, Welded, Threaded. Rows for Casing and Liner.

Final location of shoe(s) 420

(7) PERFORATIONS/SCREENS: Table with columns: From, To, Slot size, Number, Diameter, Tele/pipe size, Casing, Liner. Includes SKILLSAW method.

(8) WELL TESTS: Minimum testing time is 1 hour

Table for well tests with columns: Pump/Bailer/Air/Flowing Artesian, Yield gal/min, Drawdown, Drill stem at, Time. Includes values like 100+, 80, 415, 140, 1 hr, .5.

T.D.S. 273 MG/L PH 7.6 CONDUCTIVITY 420
Temperature of water 56° Depth Artesian Flow Found
Was a water analysis done? [X] Yes By whom DRILLER
Did any strata contain water not suitable for intended use? [ ] Too little
[ ] Salty [ ] Muddy [ ] Odor [ ] Colored [ ] Other
Depth of strata:

(9) LOCATION OF WELL by legal description:
County POLK Latitude Longitude
Township 6S N or S Range 4W E or W. WM.
Section 13 NE 1/4 SW 1/4
Tax Lot 404 Lot Block Subdivision
Street Address of Well (or nearest address)
4780 BETHEL HEIGHTS RD. NW. SALEM, OR

(10) STATIC WATER LEVEL:
11 ft. below land surface. Date 7-13-98
Artesian pressure lb. per square inch. Date

(11) WATER BEARING ZONES: Table with columns: From, To, Estimated Flow Rate, SWL. Rows for 15, 418, 17, 425, 12, 100+, 6, 11.

(12) WELL LOG: Ground Elevation

Table for well log with columns: Material, From, To, SWL. Lists various soil and rock layers like soil red, clay red sticky, basalt red very decmgsd, etc.

Date started 7-1-98 Completed 7-13-98

(unbonded) Water Well Constructor Certification:
I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

Signed [Signature] WWC Number 1487 Date 7-20-98

(bonded) Water Well Constructor Certification:
I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.


Signed [Signature] WWC Number 688 Date 7-20-98

RECEIVED

JUL 24 1998

WATER RESOURCES DEPT.  
SALEM, OREGON

polk  
50658



36728 S. Kropf Rd., Molalla, OR 97038 • Phone: (503) 829-2526 FAX (503) 829-7514

WILLAMETTE INDUSTRIES INC.  
POLK T6S R4W SEC.13 NE $\frac{1}{4}$  SW $\frac{1}{4}$   
TAX LOT# 404  
4780 BETHEL HEIGHTS RD. NW  
SALEM, OR

MATERIAL	FROM	TO
basalt brn vesc. very weak fine texture	178	210
basalt grey seamy weak fine texture	210	229
basalt grey hard broken	229	238
basalt grey brn weak broken	238	243
basalt grey hard	243	245
basalt brn vesc. med	245	262
basalt grey weak some clay grey	262	279
basalt grey hard	279	281
basalt grey med fractured slightly	281	293
basalt grey hard fractured slightly	293	341
basalt grey hard	341	345
basalt grey fractured	345	388
clay grey gritty	388	391
clay brown soft	391	395
clay grey stiff	395	402
clay stiff blue grey	402	418
sandstone hard broken	418	435