POLK 53022

STATE OF OREGON WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

| WELL I.D. # L 9838 | 386 | 98 | T. | # | LD. | J. | VEI | ν |
|--------------------|-----|----|----|---|-----|----|-----|---|
|--------------------|-----|----|----|---|-----|----|-----|---|

| START | CARD# | 1009047 | |
|-------|-------|---------|--|
| SIANI | CARD# | | |

| (1) LAND OWNER Name Bogdan Caeau State Or Zip 97202 |
|--|
| City Portland |
| Content |
| Deepening Alteration (repair/recondition) Abandonment Conversion |
| Company Community Cable Auger Cable Mud Community Industrial Irrigation Cable Mud Cable Community Industrial Irrigation Cable Mud Cable Community Industrial Irrigation Cable Mud Cable Community Cable Community Cable Community Cable Cable Mud Cable Mud Cable Cable Mud Cable Mud Cable Cable Mud Cable Cable Mud Cable Cable Mud Cable Cable Mud Cable Mud Cable Cable Mud Cable Mud Cable Cable Mud Cable Mu |
| Street Address of Well (or nearest address) East of 2557 Liberty Rd. |
| A PROPOSED USE |
| Artesian pressure Ib. per square inch Date |
| Comparison Com |
| SEAL Second Sec |
| Diameter From To Material From To Sacks or Pounds 10" 0 23 bentonite 0 23 12 sacks |
| Diameter From To Material From To Sacks or Pounds 10" 0 23 12 sacks |
| Claystone, grey, med, fractured Dots D |
| How was seal placed: Method A B C D E Other bentonite poured dry and hydrated Backfill placed from ft. to ft. Material Topsoil 0 1 Clay, brown 1 3 Clay, brown 1 3 Clay, brown 1 3 Claystone, grey, med 17 Claystone, grey, med 50 Claystone, grey, med 17 Claystone, grey, med, fractured 105 Liner: 4" -1 287 #160 D Claystone, grey, med/hard w/ occ. fractures Drive Shoe used Inside Outside None None None None None None None None |
| Other bentonite poured dry and hydrated |
| Other bentonite poured dry and hydrated |
| Backfill placed from |
| Casing: 6" |
| Casing: 6" |
| Casing: 6" +1 24 .250 |
| Casing: 6" +1 24 .250 .250 . |
| Claystone, grey, med 50 105 15 |
| Drive Shoe used Inside Outside None Claystone grey, med/hard w/occ. hard stringers 255 295 15 |
| Drive Shoe used Inside Outside None Claystone grey, med/hard w/occ. hard stringers 255 295 15 |
| Drive Shoe used Inside Outside None Claystone grey, med/hard w/occ. hard stringers 255 295 15 |
| Drive Shoe used Inside Outside None Claystone grey, med/hard w/occ. hard stringers 255 295 15 |
| |
| |
| Dickerson Well Drilling, Inc. |
| (7) PERFORATIONS/SCREENS Perforations Method skillsaw (503)623-2664 |
| Towns Year 1 DVC |
| Date Started 12-14-09 Completed 12-16-09 |
| From To Slot Number Diameter Tele/pipe Casing Liner Size size (unbonded) Water Well Constructor Certification |
| 10 110 6" 120 1/8" 4" I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well |
| 187 287 6" 120 1/8" 4" abandonment of this well is in compliance with Olegon water supply well construction standards. Materials used and information reported above are true to |
| 10 110 6" 120 1/8" 4" |
| WWC Number 1574 Page 12-19-09 |
| (8) WELL TESTS: Minimum testing time is 1 hour Pump Bailer Air Flowing Artesian Signed |
| Yield gal/min Drawdown Drill stem at Time (bonded) Water Well Constructor Certification |
| 3 N/A 287 1hr I accept responsibility for the construction, deepening, alteration, or |
| abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water |
| supply well construction standards. This report is true to the best of my knowledge |
| Temperature of water 52 Depth Artesian Flow Found and belief. |
| Was a water analysis done? Yes By whom RECEIVED Too little Did any strata contain water not suitable for intended EVED Too little WWC Number 1571 Date 12-19-09 |
| Salty Muddy ☐ Odor ☐ Colored ☐ Other |
| □ Saity □ Muddy □ Odor □ Colored □ Other □ DEC 2 3 2009 Signed □ William A Blui |